

Package ‘PxWebApiData’

October 12, 2022

Type Package

Title PX-Web Data by API

Version 0.7.0

Date 2021-10-11

Maintainer Øyvind Langsrud <oyl@ssb.no>

Imports httr, rjstat, jsonlite, pxweb

VignetteBuilder knitr

Suggests knitr, rmarkdown, testthat

Description

Function to read PX-Web data into R via API. The example code reads data from the three national statistical institutes, Statistics Norway, Statistics Sweden and Statistics Finland.

License Apache License 2.0 | file LICENSE

Encoding UTF-8

URL <https://github.com/statisticsnorway/PxWebApiData>

BugReports <https://github.com/statisticsnorway/PxWebApiData/issues>

RoxygenNote 7.1.2

NeedsCompilation no

Author Øyvind Langsrud [aut, cre],
Jan Bruusgaard [aut],
Solveig Bjørkholt [ctb],
Susie Jentoft [ctb]

Repository CRAN

Date/Publication 2021-10-11 17:00:05 UTC

R topics documented:

ApiData	2
Index	7

ApiData

PX-Web Data by API

Description

A function to read PX-Web data into R via API. The example code reads data from the three national statistical institutes, Statistics Norway, Statistics Sweden and Statistics Finland.

Usage

```
ApiData(  
  urlToData,  
  ...,  
  getDataByGET = FALSE,  
  returnMetaData = FALSE,  
  returnMetaValues = FALSE,  
  returnMetaFrames = FALSE,  
  returnApiQuery = FALSE,  
  defaultJSONquery = c(1, -2, -1),  
  verbosePrint = FALSE,  
  use_factors = FALSE,  
  urlType = "SSB",  
  apiPackage = "httr",  
  dataPackage = "rjstat",  
  returnDataSet = NULL,  
  makeNAstatus = TRUE  
)  
  
GetApiData(..., getDataByGET = TRUE)  
  
pxwebData(..., apiPackage = "pxweb", dataPackage = "pxweb")  
  
PxData(..., apiPackage = "pxweb", dataPackage = "rjstat")  
  
ApiData1(..., returnDataSet = 1)  
  
ApiData2(..., returnDataSet = 2)  
  
ApiData12(..., returnDataSet = 12)  
  
GetApiData1(..., returnDataSet = 1)  
  
GetApiData2(..., returnDataSet = 2)  
  
GetApiData12(..., returnDataSet = 12)  
  
pxwebData1(..., returnDataSet = 1)
```

```

pxwebData2(..., returnDataSet = 2)
pxwebData12(..., returnDataSet = 12)
PxData1(..., returnDataSet = 1)
PxData2(..., returnDataSet = 2)
PxData12(..., returnDataSet = 12)

```

Arguments

urlToData	url to data or id of SSB data
...	specification of JSON query for each variable
getDataByGET	When TRUE, readymade dataset by GET
returnMetaData	When TRUE, metadata returned
returnMetaValues	When TRUE, values from metadata returned
returnMetaFrames	When TRUE, values and valueTexts from metadata returned as data frames
returnApiQuery	When TRUE, JSON query returned
defaultJSONquery	specification for variables not included in ...
verbosePrint	When TRUE, printing to console
use_factors	Parameter to <code>fromJSONstat</code> defining whether dimension categories should be factors or character objects.
urlType	Parameter defining how url is constructed from id number. Currently two Statistics Norway possibilities: "SSB" (Norwegian) or "SSBen" (English)
apiPackage	Package used to capture json(-stat) data from API: "httr" (default) or "pxweb"
dataPackage	Package used to transform json(-stat) data to data frame: "rjstat" (default) or "pxweb"
returnDataSet	<p>Possible non-NULL values are 1, 2 and 12. Then a single data set is returned as a data frame.</p> <ul style="list-style-type: none"> • 1: The first data set • 2: The second data set • 12: Both data sets combined <p>The original list names are included as a comment attribute.</p>
makeNAstatus	When TRUE and when dataPackage is "rjstat" and when missing entries in value, the function tries to add an additional variable, named NAstatus, with status codes.

Details

Each variable is specified by using the variable name as input parameter. The value can be specified as: TRUE (all), FALSE (eliminated), imaginary value (top), variable indices, original variable id's (values) or variable labels (valueTexts). Reversed indices can be specified as negative values. Indices outside the range are removed. Variables not specified is set to the value of defaultJSONquery whose default means the first and the two last elements.

The value can also be specified as a (unnamed) two-element list corresponding to the two query elements, filter and values. In addition it possible with a single-element list. Then filter is set to 'all'. See examples.

Functionality in the package pxweb can be utilized by making use of the parameters apiPackage and dataPackage as implemented as the wrappers PxData and pxwebData. With data sets too large for ordinary downloads, PxData can solve the problem (multiple downloads). When using pxwebData, data will be downloaded in px-json format instead of json-stat and the output data frame will be organized differently (ContentsCode categories as separate variables).

Value

list of two data sets (label and id)

Note

See the package vignette for aggregations using filter agg.

Examples

```
##### Readymade dataset by GET. Works for readymade datasets and "saved-JSON-stat-query-links".
x <- ApiData("https://data.ssb.no/api/v0/dataset/1066.json?lang=en", getDataByGET = TRUE)
x[[1]] # The label version of the data set
x[[2]] # The id version of the data set
names(x)

##### As above with single data set output
url <- "https://data.ssb.no/api/v0/dataset/1066.json?lang=en"
x1 <- ApiData1(url, getDataByGET = TRUE) # as x[[1]]
x2 <- ApiData2(url, getDataByGET = TRUE) # as x[[2]]
comment(x1) # as names(x)[1]
comment(x2) # as names(x)[2]
ApiData12(url, getDataByGET = TRUE) # Combined

##### Special output
ApiData("https://data.ssb.no/api/v0/en/table/11419", returnMetaData = TRUE) # meta data
ApiData("https://data.ssb.no/api/v0/en/table/11419", returnMetaValues = TRUE) # meta data values
ApiData("https://data.ssb.no/api/v0/en/table/11419", returnMetaFrames = TRUE) # list of data frames
ApiData("https://data.ssb.no/api/v0/en/table/11419", returnApiQuery = TRUE) # query using defaults

##### Ordinary use      (makeNAstatus is in use in first two examples)

# NACE2007 as imaginary value (top 10), ContentsCode as TRUE (all), Tid is default
```

```

ApiData("https://data.ssb.no/api/v0/en/table/11419", NACE2007 = 10i, ContentsCode = TRUE)

# Two specified and the last is default (as above) - in Norwegian change en to no in url
ApiData("https://data.ssb.no/api/v0/no/table/11419", NACE2007 = 10i, ContentsCode = TRUE)

# Number of residents (bosatte) last year, each region
ApiData("https://data.ssb.no/api/v0/en/table/04861", Region = TRUE,
        ContentsCode = "Bosatte", Tid = 1i)

# Number of residents (bosatte) each year, total
ApiData("https://data.ssb.no/api/v0/en/table/04861", Region = FALSE,
        ContentsCode = "Bosatte", Tid = TRUE)

# Some years
ApiData("https://data.ssb.no/api/v0/en/table/04861", Region = FALSE,
        ContentsCode = "Bosatte", Tid = c(1, 5, -1))

# Two selected regions
ApiData("https://data.ssb.no/api/v0/en/table/04861", Region = c("1103", "0301"),
        ContentsCode = 2, Tid = c(1, -1))

##### Using id instead of url, unnamed input and verbosePrint
ApiData(4861, c("1103", "0301"), 1, c(1, -1)) # same as below
ApiData(4861, Region = c("1103", "0301"), ContentsCode=2, Tid=c(1, -1))
names(ApiData(4861,returnMetaFrames = TRUE)) # these names from metadata assumed two lines above
ApiData("4861", c("1103", "0301"), 1, c(1, -1), urlType="SSBen")
ApiData("01222", c("1103", "0301"), c(4, 9:11), 2i, verbosePrint = TRUE)
ApiData(1066, getDataByGET = TRUE, urlType="SSB")
ApiData(1066, getDataByGET = TRUE, urlType="SSBen")

##### Advanced use using list. See details above. Try returnApiQuery=TRUE on the same examples.
ApiData(4861, Region = list("03*"), ContentsCode = 1, Tid = 5i) # "all" can be dropped from the list
ApiData(4861, Region = list("all", "03*"), ContentsCode = 1, Tid = 5i) # same as above
ApiData(04861, Region = list("item", c("1103", "0301")), ContentsCode = 1, Tid = 5i)

##### Using data from SCB to illustrate returnMetaFrames
urlSCB <- "https://api.scb.se/OV0104/v1/doris/sv/ssd/BE/BE0101/BE0101A/BefolkningNy"
mf <- ApiData(urlSCB, returnMetaFrames = TRUE)
names(mf) # All the variable names
attr(mf, "text") # Corresponding text information as attribute
mf$ContentsCode # Data frame for the fifth variable (alternatively mf[[5]])
attr(mf,"elimination") # Finding variables that can be eliminated
ApiData(urlSCB, # Eliminating all variables that can be eliminated (line below)
        Region = FALSE, Civilstand = FALSE, Alder = FALSE, Kon = FALSE,
        ContentsCode = "BE0101N1", # Selecting a single ContentsCode by text input
        Tid = TRUE) # Choosing all possible values of Tid.

##### Using data from Statfi to illustrate use of input by variable labels (valueTexts)
urlStatfi <- "https://pxnet2.stat.fi/PXWeb/api/v1/en/StatFin/vrm/kuol/statfin_kuol_pxt_12au.px"

```

```
ApiData(urlStatfi, returnMetaFrames = TRUE)$Tiedot
ApiData(urlStatfi, Alue = FALSE, Vuosi = TRUE, Tiedot = "Population") # same as Tiedot = 21

##### Wrappers PxData and pxwebData

# Exact same output as ApiData
PxData(4861, Region = "0301", ContentsCode = TRUE, Tid = c(1, -1))

# Data organized differently
pxwebData(4861, Region = "0301", ContentsCode = TRUE, Tid = c(1, -1))

# Large query. ApiData will not work.
if(FALSE){ # This query is "commented out"
  z <- PxData("https://api.scb.se/OV0104/v1/doris/sv/ssd/BE/BE0101/BE0101A/BefolkningNy",
             Region = TRUE, Civilstand = TRUE, Alder = 1:10, Kon = FALSE,
             ContentsCode = "BE0101N1", Tid = 1:10, verbosePrint = TRUE)
}

##### Small example where makeNAstatus is in use
ApiData("04469", Tid = "2020", ContentsCode = 1, Alder = TRUE, Region = "3011")
```

Index

[ApiData](#), [2](#)

[ApiData1 \(ApiData\)](#), [2](#)

[ApiData12 \(ApiData\)](#), [2](#)

[ApiData2 \(ApiData\)](#), [2](#)

[fromJSONstat](#), [3](#)

[GetApiData \(ApiData\)](#), [2](#)

[GetApiData1 \(ApiData\)](#), [2](#)

[GetApiData12 \(ApiData\)](#), [2](#)

[GetApiData2 \(ApiData\)](#), [2](#)

[PxData \(ApiData\)](#), [2](#)

[PxData1 \(ApiData\)](#), [2](#)

[PxData12 \(ApiData\)](#), [2](#)

[PxData2 \(ApiData\)](#), [2](#)

[pxwebData \(ApiData\)](#), [2](#)

[pxwebData1 \(ApiData\)](#), [2](#)

[pxwebData12 \(ApiData\)](#), [2](#)

[pxwebData2 \(ApiData\)](#), [2](#)