

# Package ‘cabinets’

August 29, 2020

**Title** Project Specific Workspace Organization Templates

**Version** 0.5.0

**Description** Creates project specific directory and file templates that are written to a .Rprofile file. Upon starting a new R session, these templates can be used to streamline the creation of new directories that are standardized to the user's preferences.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.0

**URL** <https://github.com/nt-williams/cabinets>

**BugReports** <https://github.com/nt-williams/cabinets/issues>

**Imports** glue, R6, rstudioapi, crayon, fs, stringr, utils, git2r, cli

**Suggests** testthat (>= 2.1.0), withr

**NeedsCompilation** no

**Author** Nick Williams [aut, cre] (<<https://orcid.org/0000-0002-1378-4831>>)

**Maintainer** Nick Williams <[ntwilliams.personal@gmail.com](mailto:ntwilliams.personal@gmail.com)>

**Repository** CRAN

**Date/Publication** 2020-08-29 13:40:02 UTC

## R topics documented:

cabinets	2
cabinets_options_set	2
create_cabinet	3
delete_cabinet	4
edit_r_profile	4
FileCabinet	4
get_cabinets	6
new_cabinet_proj	6

<b>Index</b>	<b>8</b>
--------------	----------

---

cabinets

*Streamlined organization with project specific custom templates*

---

### Description

Cabinets makes it easy to create project specific file structure templates that can be referenced at the start of any R session. Cabinets works by writing project specific file templates to the .Rprofile file of the default working directory. Doing so allows the templates to be accessed in new R sessions without having to redefine them. On first use, users will be prompted for explicit permission to write to .Rprofile. Permission to write can be revoked at any time by setting the permission option in the .Rprofile file to FALSE. Due to these explicit permission requirements, cabinets will only work in interactive R sessions.

---

cabinets\_options\_set *Set cabinets options*

---

### Description

Set cabinets options

### Usage

```
cabinets_options_set(..., .envir = NULL)
```

### Arguments

...	Options to be set
.envir	Environment to set options in; if NULL, will use environment at parent.frame()

### Details

Mainly used for specifying if cabinets has permission to write to .Rprofile. Permission can be revoked at any time by opening the .Rprofile file and setting "cabinets.permission" = FALSE.

### Value

If no options are set, returns the options specified in options.

---

create_cabinet	<i>Create a cabinet template</i>
----------------	----------------------------------

---

### Description

create\_cabinet writes code to the .Rprofile file so that when new R sessions are started, the newly created cabinet, an R6 object of class FileCabinet, is available in the global environment as a hidden object. The cabinet simply stores file location and file template information that new\_cabinet\_proj uses to create new projects with the pre-defined structure.

### Usage

```
create_cabinet(name, directory, structure, .alias = name)
```

### Arguments

name	Name of the cabinet; character of length 1. This is how the cabinet will be referenced, so best to chose something memorable.
directory	The file path for where the cabinet will exist.
structure	A list of paths of folders/files to create. See details for further explanation.
.alias	An optional name for the object the cabinet will be stored in R as. Defaults to name.

### Details

Before writing to or creating a .Rprofile file, cabinets will explicitly ask for the user's permission to on exit. The cabinet structure should be defined using a list with the names defining folder paths. List values should be set to NULL.

### Value

An R6 object of class FileCabinet. The code to generate this object is written to the .Rprofile file of the home directory.

### See Also

[new\\_cabinet\\_proj](#)

---

delete_cabinet	<i>Delete Cabinets</i>
----------------	------------------------

---

**Description**

Delete Cabinets

**Usage**

```
delete_cabinet(cabinet)
```

**Arguments**

cabinet	An R6 object of class Cabinet written to the .Rprofile.
---------	---

---

edit_r_profile	<i>Open .Rprofile for editing</i>
----------------	-----------------------------------

---

**Description**

edit\_r\_profile opens the .Rprofile file for editing. If the .Rprofile file doesn't exist an error message will be returned. This is essentially a wrapper function for file.edit.

**Usage**

```
edit_r_profile()
```

**Value**

A message that .Rprofile is being opened or that it doesn't exist.

---

FileCabinet	<i>R6 class for a cabinet</i>
-------------	-------------------------------

---

**Description**

Constructs an R6 class of FileCabinet. Objects of class FileCabinet contain information that is used by new\_cabinet\_proj() to create project directories.

**Public fields**

name cabinet name.

directory the path to where future directories will be created, a string.

structure the directory structure, a list.

**Methods****Public methods:**

- [FileCabinet\\$new\(\)](#)
- [FileCabinet\\$print\(\)](#)
- [FileCabinet\\$clone\(\)](#)

**Method new():***Usage:*

```
FileCabinet$new(name, directory, structure)
```

*Arguments:*

name cabinet name.

directory the path to where future directories will be created, a string.

structure the directory structure, a list.

*Details:* Create a new 'FileCabinet' object.

*Returns:* A cabinet object.

*Examples:*

```
FileCabinet$new("test", "a/path",
               list(code = NULL, 'data/derived' = NULL, 'data/source' = NULL))
```

**Method print():***Usage:*

```
FileCabinet$print()
```

*Details:* Print an object of class FileCabinet.

**Method clone():** The objects of this class are cloneable with this method.

*Usage:*

```
FileCabinet$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

**Examples**

```
## -----
## Method `FileCabinet$new`
## -----

FileCabinet$new("test", "a/path",
               list(code = NULL, 'data/derived' = NULL, 'data/source' = NULL))
```

---

get_cabinets	<i>Print available cabinets</i>
--------------	---------------------------------

---

**Description**

get\_cabinets returns objects of class FileCabinet.

**Usage**

```
get_cabinets(envir = parent.frame())
```

**Arguments**

envir            The environment to check in. The default is the global environment.

**Value**

Objects of class FileCabinet found in the global environment.

**Examples**

```
get_cabinets()
```

---

new_cabinet_proj	<i>Create a new project using a cabinet template</i>
------------------	--

---

**Description**

Generate new project directories using cabinet templates.

**Usage**

```
new_cabinet_proj(  
  cabinet,  
  project_name,  
  r_project = TRUE,  
  open = TRUE,  
  git = TRUE,  
  git_root = NULL,  
  git_ignore = NULL,  
  ...  
)
```

**Arguments**

<code>cabinet</code>	The name of the cabinet template. Available cabinets can be found using <code>get_cabinets()</code> .
<code>project_name</code>	The name of the project to store in the cabinet, a character string. Can be a file path pointing to a directory within the specified cabinet.
<code>r_project</code>	Logical, should an Rproject be created. Default is TRUE if working in RStudio (only works in RStudio).
<code>open</code>	Logical, if creating an Rproject, should that project be opened once created. Default is TRUE if working in RStudio (only works in RStudio).
<code>git</code>	Logical, should a git repository be initiated.
<code>git_root</code>	A path relative to the project to initiate the git repository. Default is NULL and the repository is initiated at the root of the project.
<code>git_ignore</code>	Character vector of files and directories to add to <code>.gitignore</code> file.
<code>...</code>	Extra arguments to pass to <code>create_r_proj</code> .

**Value**

Creates a new directory at the path specified in the cabinet template. If `r_project` is set to TRUE, a `.Rproj` file will also be created using the project name. If `open` is set to TRUE, the new R project will be opened in a new R session.

**See Also**

[create\\_cabinet](#)

# Index

`cabinets`, [2](#)  
`cabinets_options_set`, [2](#)  
`create_cabinet`, [3](#), [7](#)  
`delete_cabinet`, [4](#)  
`edit_r_profile`, [4](#)  
`FileCabinet`, [4](#)  
`get_cabinets`, [6](#)  
`new_cabinet_proj`, [3](#), [6](#)