

# Package ‘geouy’

September 17, 2020

**Type** Package

**Title** Geographic Information of Uruguay

**Version** 0.2.3

**Maintainer** Richard Detomasi <richard.detomasi@gmail.com>

**Description** The toolbox have functions to load and process geographic information for Uruguay. And extra-function to get address coordinates and orthophotos through the uruguayan 'IDE' API <<https://www.gub.uy/infraestructura-datos-espaciales/tramites-y-servicios/servicios/servicio-direcciones-geograficas>>.

**BugReports** <https://github.com/RichDeto/geouy/issues>

**License** GPL-3

**Depends** R (>= 3.4.0)

**Language** en, es

**Encoding** UTF-8

**LazyData** TRUE

**RoxygenNote** 7.1.1

**SystemRequirements** C++11, GDAL (>= 3.0.2), GEOS (>= 3.8.0), PROJ (>= 6.2.1)

**Imports** rlang, RCurl, dplyr, glue, stringr, ggplot2, ggthemes, ggspatial, methods, magrittr, fs, sf, assertthat, testthat (>= 2.1.0), viridis

**Suggests** knitr, rmarkdown, covr

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Richard Detomasi [aut, cre] (<<https://orcid.org/0000-0002-6725-0261>>),  
Ministerio de Desarrollo Social, Uruguay (MIDES) [dct],  
Infraestructura de Datos Espaciales, Uruguay (IDE) [dct],  
Servicio Geográfico Militar, Uruguay (SGM) [dct],  
Ministerio de Transporte y Obras Públicas, Uruguay (MTOPE) [dct],  
Instituto Nacional de Estadística, Uruguay (INE) [dct],  
Instituto Geográfico Militar, Uruguay (IGM) [dct],  
Ministerio de Vivienda, Ordenamiento Territorial y Medio Ambiente,  
Uruguay (MVOTMA) [dct]

Repository CRAN

Date/Publication 2020-09-17 04:40:02 UTC

## R topics documented:

add_geom . . . . .	2
geocode_ide_uy . . . . .	3
geouy . . . . .	4
is.uy32721 . . . . .	4
is.uy4326 . . . . .	5
is.uy5381 . . . . .	5
is.uy5382 . . . . .	6
load_geouy . . . . .	6
loc_agr_ine . . . . .	7
metadata . . . . .	8
metadata_wms . . . . .	8
plot_geouy . . . . .	9
where_uy . . . . .	10
which_uy . . . . .	11

<b>Index</b>	<b>12</b>
--------------	-----------

---

add_geom	<i>This function allows you to add a geom variable with a code variable of "zona", "barrio", "localidad", "segmentos", "secciones" or "departamentos".</i>
----------	--

---

### Description

This function allows you to add a geom variable with a code variable of "zona", "barrio", "localidad", "segmentos", "secciones" or "departamentos".

### Usage

```
add_geom(data, unit, variable, crs = 32721)
```

### Arguments

data	data.frame
unit	spatial unit of data, may be: "Departamentos", "Secciones", "Secc MVD 2004", "Segmentos", "Segm MVD 2004", "Segm URB INT 2004", "Zonas", "Zonas MVD 2004", "Zonas URB INT 2004", "Localidades pg", "Municipios" o "Barrios".
variable	Variable name of unit code (without duplicates)
crs	Coordinates Reference Sistem, usually in region 32721 or 4326 (default 32721)

**Details**

Disclaimer: This script is not an official INE product. Aviso: El script no es un producto oficial de INE.

**Value**

data.frame

**See Also**

Other service: [geocode\\_ide\\_uy\(\)](#), [load\\_geouy\(\)](#), [where\\_uy\(\)](#), [which\\_uy\(\)](#)

**Examples**

```
pobre_x_dpto <- as.data.frame(cbind(nomdpto = c("ARTIGAS", "DURAZNO", "FLORIDA", "LAVALLEJA"),
  Pobreza = c(0.26, 0.27, 0.07, 0.10)))
pobre_x_dpto_geo <- add_geom(data = pobre_x_dpto, unit = "Departamentos", variable = "nomdpto")
```

---

geocode\_ide\_uy

*A function to geocoding directions using IDE\_uy*

---

**Description**

A function to geocoding directions using IDE\_uy

**Usage**

```
geocode_ide_uy(x, details = F)
```

**Arguments**

x	Dataframe with unless 3 variables: dpto = corresponding to the department, loc = city / location, dir = to the address.
details	Logical value, default FALSE for X and Y variables only, if TRUE keep all variables of the service.

**Value**

The DafaFrame x with the coordinates variables append (x and y)

**See Also**

Other service: [add\\_geom\(\)](#), [load\\_geouy\(\)](#), [where\\_uy\(\)](#), [which\\_uy\(\)](#)

## Examples

```
# x1 <- cbind(dpto="Montevideo",loc="Montevideo",dir="Av. 18 de julio 1453")
# x2 <- data.frame(x1, stringsAsFactors = F)
# geocode_ide_uy(x2)
```

---

geouy

*geouy package*

---

## Description

The toolbox have functions to load and process geographic information for Uruguay.

## Details

See the README on [Github](#)

---

is.uy32721

*This function test if an 'sf' object match with Uruguay at crs = 32721.*

---

## Description

This function test if an 'sf' object match with Uruguay at crs = 32721.

## Usage

```
is.uy32721(x)
```

## Arguments

x                    An 'sf' object with the same crs as the homonym parameter

## Value

logical value based in crs parameter of the sf object

## See Also

Other crs: [is.uy4326\(\)](#), [is.uy5381\(\)](#)

## Examples

```
is.uy32721(load_geouy("Peajes"))
```

---

`is.uy4326`*This function test if an 'sf' object match with Uruguay at crs = 4326.*

---

**Description**

This function test if an 'sf' object match with Uruguay at crs = 4326.

**Usage**

```
is.uy4326(x)
```

**Arguments**

x                    An 'sf' object with the same crs as the homonym parameter

**Value**

logical value based in crs parameter of the sf object

**See Also**

Other crs: [is.uy32721\(\)](#), [is.uy5381\(\)](#)

**Examples**

```
is.uy4326(load_geouy("Peajes"))
```

---

`is.uy5381`*This function test if an 'sf' object match with Uruguay at crs = 5381.*

---

**Description**

This function test if an 'sf' object match with Uruguay at crs = 5381.

**Usage**

```
is.uy5381(x)
```

**Arguments**

x                    An 'sf' object with the same crs as the homonym parameter

**Value**

logical value based in crs parameter of the sf object

**See Also**

Other crs: [is.uy32721\(\)](#), [is.uy4326\(\)](#)

**Examples**

```
is.uy5381(load_geouy("CCZ"))
```

---

is.uy5382	<i>This function test if an 'sf' object match with Uruguay at crs = 5382.</i>
-----------	---

---

**Description**

This function test if an 'sf' object match with Uruguay at crs = 5382.

**Usage**

```
is.uy5382(x)
```

**Arguments**

x                    An 'sf' object with the same crs as the homonym parameter

**Value**

logical value based in crs parameter of the sf object

**Examples**

```
is.uy5382(load_geouy("Dptos"))
```

---

load_geouy	<i>This function allows to take oficial uruguayan geometries, as object "sf", from various servers.</i>
------------	---

---

**Description**

This function allows to take oficial uruguayan geometries, as object "sf", from various servers.

**Usage**

```
load_geouy(c, crs = 32721, folder = tempdir())
```

**Arguments**

<code>c</code>	Define the geometries to download: may be: "Departamentos", "Secciones", "Zonas", etc. View(metadata) for details.
<code>crs</code>	Define the Coordinate Reference Systems you want the output, default 32721
<code>folder</code>	Folder where are the files download if formato == "zip" in metadata. Default tempdir()

**Value**

sf object with the requested geometries

**See Also**

Other service: [add\\_geom\(\)](#), [geocode\\_ide\\_uy\(\)](#), [where\\_uy\(\)](#), [which\\_uy\(\)](#)

**Examples**

```
secc <- load_geouy(c = "Secciones")
```

---

loc_agr_ine	<i>INE "Localidades Agregadas"</i>
-------------	------------------------------------

---

**Description**

A dataset containing the cods, names and others attributes of urban locations for Uruguay.

**Usage**

```
loc_agr_ine
```

**Format**

A data frame with 615 rows and 8 variables:

**depto** name of the "Departamento"  
**nomloc** name of the "Localidad"  
**codloc** code of the "Localidad"  
**pob2011** Population by "Censo 2011"  
**dens2011km** Population density by "Censo 2011" (population/km)  
**Nom\_loc\_agr\_13** name of the "Localidades agrupadas" (2013)  
**Loc\_agr\_13** code of the "Localidades agrupadas" (2013)  
**cat\_loc\_agr** Typical categories of "Localidades"

**See Also**

Other data: [metadata\\_wms](#), [metadata](#)

---

metadata

*Metadata of geoservices for Uruguay*

---

### Description

A dataset containing the urls and other attributes of geoservices for Uruguay.

### Usage

metadata

### Format

A data frame with 18 rows and 9 variables:

**capa** name of the geoservice

**productor** name of the institution produced the data

**repositor** name of the institution that serves the data

**crs** Coordinate Reference Systems of data

**formato** name of the institution producing the data

**anio** year of data production

**url** url of the service

**cod** name of the variable that contains the cod value of the geometries

**name** name of the variable that contains the name of the geometries

### See Also

Other data: [loc\\_agr\\_ine](#), [metadata\\_wms](#)

---

metadata\_wms

*Metadata of WMS for Uruguay*

---

### Description

A dataset containing the urls and other attributes of geoservices for Uruguay.

### Usage

metadata\_wms



**Format**

A data frame with 7 rows and 3 variables:

**capa** name of the geoservice

**formato** name of the institution producing the data

**url** url of the service

**See Also**

Other data: [loc\\_agr\\_ine](#), [metadata](#)

---

plot\_geouy

*plot\_geouy*

---

**Description**

This function allows you to set ggplot2 theme in our suggested format.

**Usage**

```
plot_geouy(x, col, viri_opt = "plasma", l = NULL, other_lab = NULL, ...)
```

**Arguments**

x	An sf object like load_geouy() results
col	Variable of "x" to plot (character)
viri_opt	A character string indicating the colormap option to use. Four options are available: "magma" (or "A"), "inferno" (or "B"), "plasma" (or "C"), "viridis" (or "D", the default option) and "cividis" (or "E")
l	If NULL none label added, if "%" porcentaje with 1 decimal labels, if "n" the value is the label, if "c" put other variable in other_lab. Default NULL
other_lab	If l is "c" put here the variable name for the labels.
...	All parameters allowed from ggplot2 themes.

**Value**

ggplot object of a choropleth map with x geometries and col values.

**Examples**

```
secc <- load_geouy("Secciones")
plot_geouy(x = secc, col = "AREA")
```

---

where_uy	<i>This function return an 'sf' object with the geometry of the consult id or group of ids, of an administrative units in Uruguay.</i>
----------	--

---

## Description

This function return an 'sf' object with the geometry of the consult id or group of ids, of an administrative units in Uruguay.

## Usage

```
where_uy(c = "Localidades pg", d = "cod", e, crs = 32721)
```

## Arguments

c	Define the geometries to consult: may be: "Departamentos", "Secciones", "Zonas", etc. View(metadata) for details.
d	A vector who determines the variables to be consult, with two options: "cod" or "name". Default "cod".
e	A vector who determines the ids or names to identify.
crs	Define the Coordinate Reference Systems you want the output, default 32721

## Value

sf object with the geometries of the d ids

## See Also

Other service: [add\\_geom\(\)](#), [geocode\\_ide\\_uy\(\)](#), [load\\_geouy\(\)](#), [which\\_uy\(\)](#)

## Examples

```
x <- where_uy(c = "Localidades pg", d = "cod", e = c(1120, 2220))
```

---

which_uy	<i>This function allows to add to an 'sf' object its spatial coincidence with one or more administrative units in Uruguay, generating the corresponding variables.</i>
----------	--

---

### Description

This function allows to add to an 'sf' object its spatial coincidence with one or more administrative units in Uruguay, generating the corresponding variables.

### Usage

```
which_uy(x, c = c("Localidades pg", "Departamentos"), d = c("cod", "name"))
```

### Arguments

x	An 'sf' object with the same crs as the homonym parameter
c	Define the geometries to download: may be: "Departamentos", "Secciones", "Zonas", etc. View(metadata) for details.
d	A vector who determines the variables to be added, with three options: "cod", "name", or "full". Default c("cod", "name").

### Value

sf object with the x geometries, with d variables requested from c added

### See Also

Other service: [add\\_geom\(\)](#), [geocode\\_ide\\_uy\(\)](#), [load\\_geouy\(\)](#), [where\\_uy\(\)](#)

### Examples

```
x <- load_geouy("Peajes")
x1 <- which_uy(x, c = "Localidades pg")
```

# Index

- \* **CRS**
  - is.uy32721, [4](#)
  - is.uy4326, [5](#)
  - is.uy5381, [5](#)
  - is.uy5382, [6](#)
- \* **IDE\_uy**
  - geocode\_ide\_uy, [3](#)
- \* **IDE**
  - load\_geouy, [6](#)
  - where\_uy, [10](#)
  - which\_uy, [11](#)
- \* **INE**
  - load\_geouy, [6](#)
  - where\_uy, [10](#)
  - which\_uy, [11](#)
- \* **MIDES**
  - load\_geouy, [6](#)
  - where\_uy, [10](#)
  - which\_uy, [11](#)
- \* **Uruguay**
  - is.uy32721, [4](#)
  - is.uy4326, [5](#)
  - is.uy5381, [5](#)
  - is.uy5382, [6](#)
- \* **crs**
  - is.uy32721, [4](#)
  - is.uy4326, [5](#)
  - is.uy5381, [5](#)
- \* **datasets**
  - loc\_agr\_ine, [7](#)
  - metadata, [8](#)
  - metadata\_wms, [8](#)
- \* **data**
  - loc\_agr\_ine, [7](#)
  - metadata, [8](#)
  - metadata\_wms, [8](#)
- \* **geocoding**
  - geocode\_ide\_uy, [3](#)
- \* **ggplot2**
  - plot\_geouy, [9](#)
- \* **maps**
  - plot\_geouy, [9](#)
- \* **plot**
  - plot\_geouy, [9](#)
- \* **service**
  - add\_geom, [2](#)
  - geocode\_ide\_uy, [3](#)
  - load\_geouy, [6](#)
  - where\_uy, [10](#)
  - which\_uy, [11](#)
- \* **sf**
  - is.uy32721, [4](#)
  - is.uy4326, [5](#)
  - is.uy5381, [5](#)
  - is.uy5382, [6](#)
  - plot\_geouy, [9](#)
- add\_geom, [2](#), [3](#), [7](#), [10](#), [11](#)
- geocode\_ide\_uy, [3](#), [3](#), [7](#), [10](#), [11](#)
- geouy, [4](#)
- is.uy32721, [4](#), [5](#), [6](#)
- is.uy4326, [4](#), [5](#), [6](#)
- is.uy5381, [4](#), [5](#), [5](#)
- is.uy5382, [6](#)
- load\_geouy, [3](#), [6](#), [10](#), [11](#)
- loc\_agr\_ine, [7](#), [8](#), [9](#)
- metadata, [7](#), [8](#), [9](#)
- metadata\_wms, [7](#), [8](#), [8](#)
- plot\_geouy, [9](#)
- where\_uy, [3](#), [7](#), [10](#), [11](#)
- which\_uy, [3](#), [7](#), [10](#), [11](#)