

Package ‘lotri’

October 13, 2022

Title A Simple Way to Specify Symmetric, Block Diagonal Matrices

Version 0.4.2

Maintainer Matthew L. Fidler <matthew.fidler@gmail.com>

Description Provides a simple mechanism to specify a symmetric block diagonal matrices (often used for covariance matrices). This is based on the domain specific language implemented in 'nlmixr2' but expanded to create matrices in R generally instead of specifying parts of matrices to estimate.

License GPL (>= 2)

URL <https://github.com/nlmixr2/lotri>

BugReports <https://github.com/nlmixr2/lotri/issues>

Depends R (>= 3.4.0)

Imports crayon, methods, stats, utils

Suggests ggplot2, knitr, Matrix, microbenchmark, rmarkdown, testthat

VignetteBuilder knitr

Biarch true

Config/testthat/edition 3

Encoding UTF-8

NeedsCompilation yes

RoxygenNote 7.2.0

Language en-US

Author Matthew L. Fidler [aut, cre] (<<https://orcid.org/0000-0001-8538-6691>>)

Repository CRAN

Date/Publication 2022-06-18 16:50:02 UTC

R topics documented:

as.lotri	2
lotri	3
lotriDataFrameToLotriExpression	5
lotriEst	6
lotriMat	7
lotriMatInv	8
lotriSep	9

Index	11
--------------	-----------

as.lotri	<i>As lower triangular matrix</i>
----------	-----------------------------------

Description

As lower triangular matrix

Usage

```
as.lotri(x, ..., default = "")

## S3 method for class 'matrix'
as.lotri(x, ..., default = "")

## S3 method for class 'data.frame'
as.lotri(x, ..., default = "")

## Default S3 method:
as.lotri(x, ..., default = "")
```

Arguments

x	Matrix or other data frame
...	Other factors
default	Is the default factor when no conditioning is implemented.

Value

Lower triangular matrix

Author(s)

Matthew Fidler

lotri *Easily Specify block-diagonal matrices with lower triangular info*

Description

Easily Specify block-diagonal matrices with lower triangular info

Usage

```
lotri(x, ..., envir = parent.frame(), default = "id")
```

Arguments

x	list, matrix or expression, see details
...	Other arguments treated as a list that will be concatenated then reapplied to this function.
envir	the environment in which expr is to be evaluated. May also be NULL, a list, a data frame, a pairlist or an integer as specified to sys.call .
default	Is the default factor when no conditioning is implemented.

Details

This can take an R matrix, a list including matrices or expressions, or expressions

Expressions can take the form

name ~ estimate

Or the lower triangular matrix when "adding" the names

name1 + name2 ~ c(est1, est2, est3)

The matrices are concatenated into a block diagonal matrix, like [bdiag](#), but allows expressions to specify matrices easier.

Value

named symmetric matrix useful in 'rxode2()' simulations (and perhaps elsewhere)

Author(s)

Matthew L Fidler

Examples

```
## A few ways to specify the same matrix
lotri({et2 + et3 + et4 ~ c(40,
                          0.1, 20,
                          0.1, 0.1, 30)})
```

```

## You do not need to enclose in {}
lotri(et2 + et3 + et4 ~ c(40,
                        0.1, 20,
                        0.1, 0.1, 30),
      et5 ~ 6)
## But if you do enclose in {}, you can use
## multi-line matrix specifications:

lotri({et2 + et3 + et4 ~ c(40,
                        0.1, 20,
                        0.1, 0.1, 30)
      et5 ~ 6
    })

## You can also add lists or actual R matrices as in this example:
lotri(list(et2 + et3 + et4 ~ c(40,
                        0.1, 20,
                        0.1, 0.1, 30),
          matrix(1,dimnames=list("et5","et5"))))

## Overall this is a flexible way to specify symmetric block
## diagonal matrices.

## For rxode2, you may also condition based on different levels of
## nesting with lotri; Here is an example:

mat <- lotri(lotri(iov.Ka ~ 0.5,
                  iov.Cl ~ 0.6),
            lotri(occ.Ka ~ 0.5,
                  occ.Cl ~ 0.6) | occ(lower=4,nu=3))

mat

## you may access features of the matrix simply by `$` that is

mat$lower # Shows the lower bound for each condition

mat$lower$occ # shows the lower bound for the occasion variable

## Note that `lower` fills in defaults for parameters. This is true
## for `upper` true; In fact when accessing this the defaults
## are put into the list

mat$upper

## However all other values return NULL if they are not present like

mat$lotri

## And values that are specified once are only returned on one list:

mat$nu

```

```
mat$nu$occ
mat$nu$id

## You can also change the default condition with `as.lotri`

mat <- as.lotri(mat, default="id")

mat
```

lotriDataFrameToLotriExpression

Convert a lotri data frame to a lotri expression

Description

Convert a lotri data frame to a lotri expression

Usage

```
lotriDataFrameToLotriExpression(data, useIni = FALSE)
```

Arguments

data	lotri data frame
useIni	Use 'ini' instead of 'lotri' in the expression

Value

expression of the lotri syntax equivalent to the data.frame provided

Author(s)

Matthew L. Fidler

Examples

```
x <- lotri({
  tka <- 0.45; label("Log Ka")
  tcl <- 1; label("Log Cl")
  tv <- 3.45; label("Log V")
  eta.ka ~ 0.6
  eta.cl ~ 0.3
  eta.v ~ 0.1
  add.err <- 0.7
})

df <- as.data.frame(x)
```

```
lotriDataFrameToLotriExpression(df)

# You may also call as.expression directly from the lotri object

as.expression(x)
```

lotriEst	<i>Extract or remove lotri estimate data frame from lotri object</i>
----------	--

Description

Extract or remove lotri estimate data frame from lotri object

Usage

```
lotriEst(x, drop = FALSE)
```

Arguments

x	lotri object
drop	boolean indicating if the lotri estimate should be dropped

Value

data frame with estimates or NULL if there is not a data.frame attached

Examples

```
fix1 <- lotri({
  a <- c(0, 1); backTransform("exp"); label("a label")
  b <- c(0, 1, 2)
  c <- fix(1)
  d <- fix(0, 1, 2)
  e <- c(0, 1, 2, fixed)
  f+g ~ c(1,
          0.5, 1)
})

# Extract the attached lotri estimate data frame
lotriEst(fix1)

# Remove the attached lotri estimate data frame
lotriEst(fix1, drop=TRUE)
```

lotriMat	<i>Create a matrix from a list of matrices</i>
----------	--

Description

This creates a named banded symmetric matrix from a list of named symmetric matrices.

Usage

```
lotriMat(matList, format = NULL, start = 1L)
```

Arguments

matList	list of symmetric named matrices
format	The format of dimension names when a sub-matrix is repeated. The format will be called with the dimension number, so "ETA[%d]" would represent "ETA[1]", "ETA[2]", etc
start	The number the counter of each repeated dimension should start.

Value

Named symmetric block diagonal matrix based on concatenating the list of matrices together

Author(s)

Matthew Fidler

Examples

```
testList <- list(lotri({et2 + et3 + et4 ~ c(40,
                                0.1, 20,
                                0.1, 0.1, 30)}),
                lotri(et5 ~ 6))

testList

lotriMat(testList)

# Another option is to repeat a matrix a number of times. This
# can be done with list(matrix, # times to repeat).

# In the example below, the first matrix is repeated 3 times
testList <- list(list(lotri({et2 + et3 + et4 ~ c(40,
                                0.1, 20,
                                0.1, 0.1, 30)}), 3),
                lotri(et5 ~ 6))
```

```
lotriMat(testList)

# Notice that the dimension names `et2`, `et3` and `et4` are
# repeated.

# Another option is to name the dimensions. For example it could
# be `ETA[1]`, `ETA[2]`, etc by using the 'format' option:

lotriMat(testList, "ETA[%d]")

# Or could start with ETA[2]:

lotriMat(testList, "ETA[%d]", 2)
```

lotriMatInv	<i>Converts a matrix into a list of block matrices</i>
-------------	--

Description

Converts a matrix into a list of block matrices

Usage

```
lotriMatInv(mat)
```

Arguments

mat Matrix to convert to a list of block matrices

Details

This is the inverse of ‘lotriMat()’

Value

A list of block matrixes

Author(s)

Matthew Fidler

Examples

```
# Create a block matrix using `lotri()`
mat <- lotri({
  a+b ~ c(1,
          0.5, 1)
  c ~ 1
```



```

      d + e ~ c(1,
               0.5, 1)
    })

print(mat)

# now convert t a list of matrices

mat2 <- lotriMatInv(mat)
print(mat2)

# Of course you can convert it back to a full matrix:

mat3 <- lotriMat(mat2)

print(mat3)

```

lotriSep

Separate a lotri matrix into above and below lotri matrices

Description

This is used for creating nesting simulations in ‘rxode2()’ and may not be useful for external function calls.

Usage

```
lotriSep(x, above, below, aboveStart = 1L, belowStart = 1L)
```

Arguments

x	lotri matrix
above	Named integer vector listing variability above the id level. Each element lists the number of population differences in the whole data-set (as integer)
below	Named integer vector listing variability below the id level. Each element lists the number of items below the individual level. For example with 3 occasions per individual you could use ‘c(occ=3L)’
aboveStart	Add the attribute of where THETA[#] will be added
belowStart	Add the attribute of where ETA[#] will be added

Value

List of two lotri matrices

Author(s)

Matthew Fidler

Examples

```
omega <- lotri(lotri(eta.Cl ~ 0.1,  
  eta.Ka ~ 0.1) | id(nu=100),  
  lotri(eye.Cl ~ 0.05,  
  eye.Ka ~ 0.05) | eye(nu=50),  
  lotri(iov.Cl ~ 0.01,  
  iov.Ka ~ 0.01) | occ(nu=200),  
  lotri(inv.Cl ~ 0.02,  
  inv.Ka ~ 0.02) | inv(nu=10))  
  
lotriSep(omega, above=c(inv=10L), below=c(eye=2L, occ=4L))
```

Index

`as.lotri`, 2

`bdiag`, 3

`environment`, 3

`lotri`, 3

`lotriDataFrameToLotriExpression`, 5

`lotriEst`, 6

`lotriMat`, 7

`lotriMatInv`, 8

`lotriSep`, 9

`sys.call`, 3