

Package ‘modelStudio’

September 10, 2020

Title Interactive Studio for Explanatory Model Analysis

Version 2.0.0

Description Automate the explanatory analysis of machine learning predictive models. Generate advanced interactive model explanations in the form of a serverless HTML site with only one line of code. This tool is model agnostic, therefore compatible with most of the black box predictive models and frameworks. The main function computes various (instance and dataset level) model explanations and produces a customisable dashboard, which consists of multiple panels for plots with their short descriptions. Easily save the dashboard and share it with others. Tools for Explanatory Model Analysis unite with tools for Exploratory Data Analysis to give a broad overview of the model behavior.

Depends R (>= 3.5)

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Imports DALEX (>= 2.0), ingredients (>= 2.0), iBreakDown (>= 1.3.1), r2d3, jsonlite, progress, digest

Suggests parallelMap, ranger, xgboost, knitr, rmarkdown, testthat, spelling

VignetteBuilder knitr

URL <https://modelstudio.drwhy.ai>,
<https://github.com/ModelOriented/modelStudio>

BugReports <https://github.com/ModelOriented/modelStudio/issues>

Language en-US

NeedsCompilation no

Author Hubert Baniecki [aut, cre] (<<https://orcid.org/0000-0001-6661-5364>>),
Przemyslaw Biecek [aut] (<<https://orcid.org/0000-0001-8423-1823>>),
Piotr Piatyszek [ctb]

Maintainer Hubert Baniecki <hbaniecki@gmail.com>

Repository CRAN

Date/Publication 2020-09-10 14:30:03 UTC

R topics documented:

modelStudio	2
ms_options	5
ms_update_observations	8
ms_update_options	10

Index **12**

modelStudio

Interactive Studio for Explanatory Model Analysis

Description

This function computes various (instance and dataset level) model explanations and produces a customisable dashboard, which consists of multiple panels for plots with their short descriptions. Easily save the dashboard and share it with others. Tools for [Explanatory Model Analysis](#) unite with tools for Exploratory Data Analysis to give a broad overview of the model behavior.

The extensive documentation covers:

- Function parameters description - [perks and features](#)
- Framework and model compatibility - [R & Python examples](#)
- Theoretical introduction to the plots - [Explanatory Model Analysis: Explore, Explain and Examine Predictive Models](#)

Displayed variable can be changed by clicking on the bars of plots or with the first dropdown list, and observation can be changed with the second dropdown list. The dashboard gathers useful, but not sensitive, information about how it is being used (e.g. computation length, package version, dashboard dimensions). This is for the development purposes only and can be blocked by setting telemetry to FALSE.

Usage

```
modelStudio(explainer, ...)
```

```
## S3 method for class 'explainer'
modelStudio(
  explainer,
  new_observation = NULL,
  new_observation_y = NULL,
  facet_dim = c(2, 2),
  time = 500,
  max_features = 10,
```

```

    N = 300,
    B = 10,
    eda = TRUE,
    show_info = TRUE,
    parallel = FALSE,
    options = ms_options(),
    viewer = "external",
    widget_id = NULL,
    telemetry = TRUE,
    max_vars = NULL,
    ...
  )

```

Arguments

explainer	An explainer created with DALEX::explain().
...	Other parameters.
new_observation	New observations with columns that correspond to variables used in the model.
new_observation_y	True label for new_observation (optional).
facet_dim	Dimensions of the grid. Default is c(2, 2).
time	Time in ms. Set the animation length. Default is 500.
max_features	Maximum number of features to be included in BD and SV plots. Default is 10.
N	Number of observations used for the calculation of PD and AD. 10*N is a number of observations used for the calculation of FI. Default N is 300. See vignette
B	Number of permutation rounds used for calculation of SV and FI. Default is 10. See vignette
eda	Compute EDA plots and Residuals vs Feature plot, which adds the data to the dashboard. Default is TRUE.
show_info	Verbose a progress on the console. Default is TRUE.
parallel	Speed up the computation using parallelMap::parallelMap(). See vignette . This might interfere with showing progress using show_info.
options	Customize modelStudio. See ms_options and vignette .
viewer	Default is external to display in an external RStudio window. Use browser to display in an external browser or internal to use the RStudio internal viewer pane for output.
widget_id	Use an explicit element ID for the widget (rather than an automatically generated one). Useful e.g. when using modelStudio with Shiny. See vignette .
telemetry	The dashboard gathers useful, but not sensitive, information about how it is being used (e.g. computation length, package version, dashboard dimensions). This is for the development purposes only and can be blocked by setting telemetry to FALSE.
max_vars	An alias for max_features. If provided, it will override the value.

Value

An object of the `r2d3`, `htmlwidget`, `modelStudio` class.

References

- The input object is implemented in **DALEX**
- Feature Importance, Ceteris Paribus, Partial Dependence and Accumulated Dependence explanations are implemented in **ingredients**
- Break Down and Shapley Values explanations are implemented in **iBreakDown**

See Also

Vignettes: **modelStudio - R & Python examples** and **modelStudio - perks and features**

Examples

```
library("DALEX")
library("modelStudio")

## ex1 classification on 'titanic' data

# fit a model
model_titanic <- glm(survived ~., data = titanic_imputed, family = "binomial")

# create an explainer for the model
explainer_titanic <- explain(model_titanic,
                             data = titanic_imputed,
                             y = titanic_imputed$survived,
                             label = "Titanic GLM")

# pick observations
new_observations <- titanic_imputed[1:2,]
rownames(new_observations) <- c("Lucas", "James")

# make a studio for the model
modelStudio(explainer_titanic,
            new_observations,
            N = 200, B = 5) # faster example

## ex2 regression on 'apartments' data
library("ranger")

model_apartments <- ranger(m2.price ~. ,data = apartments)

explainer_apartments <- explain(model_apartments,
                               data = apartments,
                               y = apartments$m2.price)

new_apartments <- apartments[1:2,]
```

```

rownames(new_apartments) <- c("ap1", "ap2")

# change dashboard dimensions and animation length
modelStudio(explainer_apartments,
             new_apartments,
             facet_dim = c(2, 3),
             time = 800)

# add information about true labels
modelStudio(explainer_apartments,
             new_apartments,
             new_observation_y = new_apartments$m2.price)

# don't compute EDA plots
modelStudio(explainer_apartments,
             eda = FALSE)

## ex3 xgboost model on 'HR' dataset
library("xgboost")

HR_matrix <- model.matrix(status == "fired" ~ . -1, HR)

# fit a model
xgb_matrix <- xgb.DMatrix(HR_matrix, label = HR$status == "fired")
params <- list(max_depth = 3, objective = "binary:logistic", eval_metric = "auc")
model_HR <- xgb.train(params, xgb_matrix, nrounds = 300)

# create an explainer for the model
explainer_HR <- explain(model_HR,
                       data = HR_matrix,
                       y = HR$status == "fired",
                       label = "xgboost")

# pick observations
new_observation <- HR_matrix[1:2, , drop=FALSE]
rownames(new_observation) <- c("id1", "id2")
# make a studio for the model
modelStudio(explainer_HR,
            new_observation)

```

ms_options

Modify default options and pass them to modelStudio

Description

This function returns default options for `modelStudio`. It is possible to modify values of this list and pass it to the options parameter in the main function. **WARNING: Editing default options**

may cause unintended behavior.

Usage

```
ms_options(...)
```

```
modelStudioOptions(...)
```

Arguments

... Options to change in the form option_name = value.

Value

list of options for modelStudio.

Options

Main options::

scale_plot TRUE Makes every plot the same height, ignores bar_width.

show_boxplot TRUE Display boxplots in Feature Importance and Shapley Values plots.

show_subtitle TRUE Should the subtitle be displayed?

subtitle label parameter from explainer.

ms_title Title of the dashboard.

margin_* Plot margins. Change margin_left for longer/shorter axis labels.

w 420 in px. Inner plot width.

h 280 in px. Inner plot height.

bar_width 16 in px. Default width of bars for all plots, ignored when scale_plot = TRUE.

line_size 2 in px. Default width of lines for all plots.

point_size 3 in px. Default point radius for all plots.

[bar,line,point _color] [#46bac2, #46bac2, #371ea3]

positive_color #8bdcbe for Break Down and Shapley Values bars.

negative_color #f05a71 for Break Down and Shapley Values bars.

default_color #371ea3 for Break Down bar and highlighted line.

Plot specific options:: ** is a two letter code unique to each plot, might be one of [bd, sv, cp, fi, pd, ad, rv, fd, tv, at].

****_title** Plot specific title. Default varies.

****_subtitle** Plot specific subtitle. Default is subtitle.

****_bar_width** Plot specific width of bars. Default is bar_width, ignored when scale_plot = TRUE.

****_line_size** line_size Plot specific width of lines. Default is line_size.

****_point_size** Plot specific point radius. Default is point_size.

****_*_color** Plot specific [bar, line, point] color. Default is [bar, line, point]_color.

References

- The input object is implemented in **DALEX**
- Feature Importance, Ceteris Paribus, Partial Dependence and Accumulated Dependence explanations are implemented in **ingredients**
- Break Down and Shapley Values explanations are implemented in **iBreakDown**

See Also

Vignettes: **modelStudio - R & Python examples** and **modelStudio - perks and features**

Examples

```
library("DALEX")
library("modelStudio")

# fit a model
model_apartments <- glm(m2.price ~. , data = apartments)

# create an explainer for the model
explainer_apartments <- explain(model_apartments,
                                data = apartments,
                                y = apartments$m2.price)

# pick observations
new_observation <- apartments[1:2,]
rownames(new_observation) <- c("ap1", "ap2")

# modify default options
new_options <- ms_options(
  show_subtitle = TRUE,
  bd_subtitle = "Hello World",
  line_size = 5,
  point_size = 9,
  line_color = "pink",
  point_color = "purple",
  bd_positive_color = "yellow",
  bd_negative_color = "orange"
)

# make a studio for the model
modelStudio(explainer_apartments,
            new_observation,
            options = new_options,
            N = 200, B = 5) # faster example
```

 ms_update_observations

Update the observations of a modelStudio object

Description

This function calculates local explanations on new observations and adds them to the modelStudio object.

Usage

```
ms_update_observations(
  object,
  explainer,
  new_observation = NULL,
  new_observation_y = NULL,
  max_features = 10,
  B = 10,
  show_info = TRUE,
  parallel = FALSE,
  widget_id = NULL,
  overwrite = FALSE,
  ...
)
```

Arguments

object	A modelStudio created with modelStudio().
explainer	An explainer created with DALEX::explain().
new_observation	New observations with columns that correspond to variables used in the model.
new_observation_y	True label for new_observation (optional).
max_features	Maximum number of features to be included in BD and SV plots. Default is 10.
B	Number of permutation rounds used for calculation of SV and FI. Default is 10. See vignette
show_info	Verbose a progress on the console. Default is TRUE.
parallel	Speed up the computation using parallelMap::parallelMap(). See vignette . This might interfere with showing progress using show_info.
widget_id	Use an explicit element ID for the widget (rather than an automatically generated one). Useful e.g. when using modelStudio with Shiny. See vignette .
overwrite	Overwrite existing observations and their explanations. Default is FALSE which means add new observations to the existing ones.
...	Other parameters.

Value

An object of the `r2d3`, `htmlwidget`, `modelStudio` class.

References

- The input object is implemented in **DALEX**
- Feature Importance, Ceteris Paribus, Partial Dependence and Accumulated Dependence explanations are implemented in **ingredients**
- Break Down and Shapley Values explanations are implemented in **iBreakDown**

See Also

Vignettes: **modelStudio - R & Python examples** and **modelStudio - perks and features**

Examples

```
library("DALEX")
library("modelStudio")

# fit a model
model_titanic <- glm(survived ~., data = titanic_imputed, family = "binomial")

# create an explainer for the model
explainer_titanic <- explain(model_titanic,
                             data = titanic_imputed,
                             y = titanic_imputed$survived)

# make a studio for the model
ms <- modelStudio(explainer_titanic,
                  N = 200, B = 5) # faster example

# add new observations
ms <- ms_update_observations(ms,
                             explainer_titanic,
                             new_observation = titanic_imputed[100:101,],
                             new_observation_y = titanic_imputed$survived[100:101])

ms

# overwrite the observations with new ones
ms <- ms_update_observations(ms,
                             explainer_titanic,
                             new_observation = titanic_imputed[100:101,],
                             overwrite = TRUE)

ms
```

ms_update_options	<i>Update the options of a modelStudio object</i>
-------------------	---

Description

This function updates the options of a `modelStudio` object. **WARNING: Editing default options may cause unintended behavior.**

Usage

```
ms_update_options(object, ...)
```

Arguments

<code>object</code>	A <code>modelStudio</code> created with <code>modelStudio()</code> .
<code>...</code>	Options to change in the form <code>option_name = value</code> , e.g. <code>time = 0</code> , <code>facet_dim = c(1, 2)</code> .

Value

An object of the `r2d3`, `htmlwidget`, `modelStudio` class.

Options

Main options::

scale_plot TRUE Makes every plot the same height, ignores `bar_width`.

show_boxplot TRUE Display boxplots in Feature Importance and Shapley Values plots.

show_subtitle TRUE Should the subtitle be displayed?

subtitle label parameter from explainer.

ms_title Title of the dashboard.

margin_* Plot margins. Change `margin_left` for longer/shorter axis labels.

w 420 in px. Inner plot width.

h 280 in px. Inner plot height.

bar_width 16 in px. Default width of bars for all plots, ignored when `scale_plot = TRUE`.

line_size 2 in px. Default width of lines for all plots.

point_size 3 in px. Default point radius for all plots.

[bar,line,point _color] [#46bac2, #46bac2, #371ea3]

positive_color #8bdcbe for Break Down and Shapley Values bars.

negative_color #f05a71 for Break Down and Shapley Values bars.

default_color #371ea3 for Break Down bar and highlighted line.

Plot specific options:: ** is a two letter code unique to each plot, might be one of [bd, sv, cp, fi, pd, ad, rv, fd, tv, at].

****_title** Plot specific title. Default varies.

Index

`modelStudio`, [2](#), [5](#), [10](#)
`modelStudioOptions (ms_options)`, [5](#)
`ms_options`, [3](#), [5](#)
`ms_update_observations`, [8](#)
`ms_update_options`, [10](#)