

Package ‘plsRbeta’

October 14, 2022

Version 0.2.9

Date 2022-05-02

Depends R (>= 3.5.0)

Imports mvtnorm, boot, Formula, MASS, plsRglm, betareg, methods

Enhances

Suggests bipartite, knitr, markdown, plotrix, pls, plsdoF, prettydoc, rmarkdown

Title Partial Least Squares Regression for Beta Regression Models

Author Frederic Bertrand [cre, aut] (<<https://orcid.org/0000-0002-0837-8281>>),
Myriam Maumy-Bertrand [aut] (<<https://orcid.org/0000-0002-4615-1512>>)

Maintainer Frederic Bertrand <frederic.bertrand@utt.fr>

Description Provides Partial least squares Regression for (weighted) beta regression models (Bertrand 2013, <<http://journal-sfds.fr/article/view/215>>) and k-fold cross-validation of such models using various criteria. It allows for missing data in the explanatory variables. Bootstrap confidence intervals constructions are also available.

License GPL-3

Encoding UTF-8

Classification/MSC 62J12, 62J99

LazyData true

VignetteBuilder knitr

RoxygenNote 7.1.1

URL <https://fbertran.github.io/plsRbeta/>,
<https://github.com/fbertran/plsRbeta/>

BugReports <https://github.com/fbertran/plsRbeta/issues/>

NeedsCompilation no

Repository CRAN

Date/Publication 2022-05-02 22:52:07 UTC

R topics documented:

plsRbeta-package	3
bootplsbeta	3
coefs.plsRbeta	7
coefs.plsRbeta.raw	8
coefs.plsRbetanp	10
colon	11
ind_BCa_nt1BC	17
ind_BCa_nt1BR	17
ind_BCa_nt2BC	18
ind_BCa_nt2BR	19
ind_BCa_nt3	19
ind_BCa_nt3BC	20
ind_BCa_nt3BR	21
ind_BCa_nt4BC	21
ind_BCa_nt4BR	22
ind_BCa_nt5BC	23
ind_BCa_nt5BR	23
ind_BCa_nt6BC	24
ind_BCa_nt6BR	25
kfolds2Chisq	25
kfolds2Chisqind	27
kfolds2CVinfos_beta	28
modpls.boot3	29
modpls_sub4	30
permcoefs.plsRbeta	31
permcoefs.plsRbeta.raw	32
permcoefs.plsRbetanp	34
plsRbeta	35
PLS_beta	39
PLS_beta_formula	43
PLS_beta_kfoldcv	49
PLS_beta_kfoldcv_formula	54
PLS_beta_wvc	60
print.plsRbetamodel	64
print.summary.plsRbetamodel	65
simul_data_UniYX_beta	66
summary.plsRbetamodel	68
tilt.bootplsbeta	69
TxTum	71
TxTum.mod.bootBC1	73
TxTum.mod.bootBR6	74

plsRbeta-package *plsRbeta-package*

Description

Provides Partial least squares Regression for (weighted) beta regression models (Bertrand 2013, <<http://journal-sfds.fr/article/view/215>>) and k-fold cross-validation of such models using various criteria. It allows for missing data in the explanatory variables. Bootstrap confidence intervals constructions are also available.

References

Partial least squares Regression for (weighted) beta regression models (Bertrand 2013, <<http://journal-sfds.fr/article/view/215>>), <https://github.com/fbertran/plsRbeta/> et <https://fbertran.github.io/plsRbeta/>

Examples

```
data("GasolineYield",package="betareg")
modpls <- plsRbeta(yield~.,data=GasolineYield,nt=3,modele="pls-beta")
modpls$pp
modpls$Coeffs
modpls$Std.Coeffs
modpls$InfCrit
modpls$PredictY[1,]
rm("modpls")

data("GasolineYield",package="betareg")
yGasolineYield <- GasolineYield$yield
XGasolineYield <- GasolineYield[,2:5]
modpls <- plsRbeta(yGasolineYield,XGasolineYield,nt=3,modele="pls-beta")
modpls$pp
modpls$Coeffs
modpls$Std.Coeffs
modpls$InfCrit
modpls$PredictY[1,]
rm("modpls")
```

bootplsbeta *Non-parametric Bootstrap for PLS beta regression models*

Description

Provides a wrapper for the bootstrap function boot from the boot R package. Implements non-parametric bootstrap for PLS beta regression models by case resampling.

Usage

```
bootplsbeta(
  object,
  typeboot = "plsmodel",
  R = 250,
  statistic = NULL,
  sim = "ordinary",
  stype = "i",
  stabvalue = 1e+06,
  ...
)
```

Arguments

<code>object</code>	An object of class <code>plsRbetamodel</code> to bootstrap
<code>typeboot</code>	The type of bootstrap. Either (Y,X) bootstrap (<code>typeboot="plsmodel"</code>) or (Y,T) bootstrap (<code>typeboot="fmodel_np"</code>). Defaults to (Y,T) resampling.
<code>R</code>	The number of bootstrap replicates. Usually this will be a single positive integer. For importance resampling, some resamples may use one set of weights and others use a different set of weights. In this case <code>R</code> would be a vector of integers where each component gives the number of resamples from each of the rows of weights.
<code>statistic</code>	A function which when applied to data returns a vector containing the statistic(s) of interest. <code>statistic</code> must take at least two arguments. The first argument passed will always be the original data. The second will be a vector of indices, frequencies or weights which define the bootstrap sample. Further, if predictions are required, then a third argument is required which would be a vector of the random indices used to generate the bootstrap predictions. Any further arguments can be passed to <code>statistic</code> through the <code>...</code> argument.
<code>sim</code>	A character string indicating the type of simulation required. Possible values are "ordinary" (the default), "balanced", "permutation", or "antithetic".
<code>stype</code>	A character string indicating what the second argument of <code>statistic</code> represents. Possible values of <code>stype</code> are "i" (indices - the default), "f" (frequencies), or "w" (weights).
<code>stabvalue</code>	A value to hard threshold bootstrap estimates computed from atypical resamplings.
<code>...</code>	Other named arguments for <code>statistic</code> which are passed unchanged each time it is called. Any such arguments to <code>statistic</code> should follow the arguments which <code>statistic</code> is required to have for the simulation. Beware of partial matching to arguments of <code>boot</code> listed above.

Details

More details on bootstrap techniques are available in the help of the `boot` function.

Value

An object of class "boot". See the Value part of the help of the function [boot](#).

Author(s)

Frédéric Bertrand
 <frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[boot](#)

Examples

```
data("GasolineYield",package="betareg")

# Std coefficients
modplsbeta <- plsRbeta(yield~.,data=GasolineYield,nt=3, modele="pls-beta")
GazYield.boot <- bootplsbeta(modplsbeta, sim="ordinary", stype="i", R=250)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
  type = c("norm","basic","perc","bca"), index=1)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
  type = c("norm","basic","perc","bca"), index=2)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
  type = c("norm","basic","perc","bca"), index=3)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
  type = c("norm","basic","perc","bca"), index=4)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
  type = c("norm","basic","perc","bca"), index=5)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
  type = c("norm","basic","perc","bca"), index=6)

plsRglm::boxplots.bootpls(GazYield.boot)
plsRglm::confints.bootpls(GazYield.boot)
plsRglm::plots.confints.bootpls(plsRglm::confints.bootpls(GazYield.boot))

#Raw coefficients
modplsbeta <- plsRbeta(yield~.,data=GasolineYield,nt=3, modele="pls-beta")
GazYield.boot.raw <- bootplsbeta(modplsbeta, sim="ordinary", stype="i",
R=250, statistic=coefs.plsRbeta.raw)
boot::boot.ci(GazYield.boot.raw, conf = c(0.90,0.95),
  type = c("norm","basic","perc","bca"), index=1)
```

```

boot::boot.ci(GazYield.boot.raw, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=2)
boot::boot.ci(GazYield.boot.raw, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=3)
boot::boot.ci(GazYield.boot.raw, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=4)
boot::boot.ci(GazYield.boot.raw, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=5)
boot::boot.ci(GazYield.boot.raw, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=6)

plsRglm::boxplots.bootpls(GazYield.boot)
plsRglm::confints.bootpls(GazYield.boot)
plsRglm::plots.confints.bootpls(plsRglm::confints.bootpls(GazYield.boot))

plot(GazYield.boot,index=2)
boot::jack.after.boot(GazYield.boot, index=2, useJ=TRUE, nt=3)
plot(GazYield.boot, index=2,jack=TRUE)

# PLS bootstrap balanced

GazYield.boot <- bootplsbeta(plsRbeta(yield~.,data=GasolineYield,nt=3,
modele="pls-beta"), sim="balanced", stype="i", R=250)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=1)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=2)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=3)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=4)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=5)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc","bca"), index=6)

plsRglm::boxplots.bootpls(GazYield.boot)
plsRglm::confints.bootpls(GazYield.boot)
plsRglm::plots.confints.bootpls(plsRglm::confints.bootpls(GazYield.boot))

plot(GazYield.boot)
boot::jack.after.boot(GazYield.boot, index=1, useJ=TRUE, nt=3)
plot(GazYield.boot,jack=TRUE)

# PLS permutation bootstrap

GazYield.boot <- bootplsbeta(plsRbeta(yield~.,data=GasolineYield,nt=3,
modele="pls-beta"), sim="permutation", stype="i", R=250)

```

```

boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc"), index=1)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc"), index=2)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc"), index=3)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc"), index=4)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc"), index=5)
boot::boot.ci(GazYield.boot, conf = c(0.90,0.95),
type = c("norm","basic","perc"), index=6)
plsRglm::boxplots.bootpls(GazYield.boot)
plot(GazYield.boot)

```

coefs.plsRbeta

Coefficients function for bootstrap techniques

Description

Returns the coefficients of a "plsRbeta" model.

Usage

```

coefs.plsRbeta(
  dataset,
  ind,
  nt,
  modele,
  family = NULL,
  method = "logistic",
  link = NULL,
  link.phi = NULL,
  type = "ML",
  verbose = TRUE
)

```

Arguments

dataset	dataset to resample
ind	indices for resampling
nt	number of components to use
modele	name of the PLS glm or PLS beta model to be fitted ("pls", "pls-glm-Gamma", "pls-glm-gaussian", "pls-glm-inverse.gaussian", "pls-glm-logistic", "pls-glm-poisson", "pls-glm-polr", "pls-beta"). Use "modele=pls-glm-family" to enable the family option.

family	family to use if GLM model, see plsRbeta
method	method for beta regression
link	link for beta regression
link.phi	link.phi for beta regression
type	type of estimates
verbose	should info messages be displayed ?

Value

Coefficients' Estimates on a sample.

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFDs/article/view/215>

See Also

See also [bootplsbeta](#).

Examples

```
data("GasolineYield", package="betareg")
modpls <- coefs.plsRbeta(GasolineYield[, -6], 1:32, nt=3, modele="pls-beta")
```

coefs.plsRbeta.raw *Raw coefficients function for bootstrap techniques*

Description

Returns the coefficients of a "plsRbeta" model.

Usage

```

coefs.plsRbeta.raw(
  dataset,
  ind,
  nt,
  modele,
  family = NULL,
  method = "logistic",
  link = NULL,
  link.phi = NULL,
  type = "ML",
  verbose = TRUE
)

```

Arguments

dataset	dataset to resample
ind	indices for resampling
nt	number of components to use
modele	name of the PLS glm or PLS beta model to be fitted ("pls", "pls-glm-Gamma", "pls-glm-gaussian", "pls-glm-inverse.gaussian", "pls-glm-logistic", "pls-glm-poisson", "pls-glm-polr", "pls-beta"). Use "modele=pls-glm-family" to enable the family option.
family	family to use if GLM model, see plsRbeta
method	method for beta regression
link	link for beta regression
link.phi	link.phi for beta regression
type	type of estimates
verbose	should info messages be displayed ?

Value

Coefficients' Estimates on a sample.

Author(s)

Frédéric Bertrand
 <frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

See also [bootplsbeta](#).

Examples

```
data("GasolineYield", package="betareg")
modpls <- coefs.plsRbeta.raw(GasolineYield[,-6], 1:32, nt=3, modele="pls-beta")
```

 coefs.plsRbetanp

Coefficients for bootstrap computations of PLSBeta models

Description

A function passed to boot to perform bootstrap.

Usage

```
coefs.plsRbetanp(
  dataRepYtt,
  ind,
  nt,
  modele,
  family = NULL,
  maxcoefvalues,
  wwetoile,
  ifbootfail
)
```

Arguments

dataRepYtt	components' coordinates to bootstrap
ind	indices for resampling
nt	number of components to use
modele	type of modele to use, see plsRbeta
family	glm family to use, see plsRbeta
maxcoefvalues	maximum values allowed for the estimates of the coefficients to discard those coming from singular bootstrap samples
wwetoile	values of the Wstar matrix in the original fit
ifbootfail	value to return if the estimation fails on a bootstrap sample

Value

estimates on a bootstrap sample or ifbootfail value if the bootstrap computation fails.

Note

~~some notes~~

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

See Also

See also [bootplsbeta](#)

Examples

```
data("GasolineYield", package="betareg")
bootplsbeta(plsRbeta(yield~., data=GasolineYield, nt=3, modele="pls-beta"),
R=250, statistic=coefs.plsRbetanp)
```

colon

Tumor rate and spectral data

Description

This dataset feature tumor rate data with spectral data descriptors. It is used as an example in the second vignette of the package.

Usage

```
colon
```

Format

A data frame with 80 observations on the following 180 variables.

X..Tumor.Cells a numeric vector

X4.69499969 a numeric vector

X4.68499947 a numeric vector

X4.67499971 a numeric vector

X4.66499949 a numeric vector

X4.65499973 a numeric vector

X4.64499995 a numeric vector

X4.63499975 a numeric vector

X4.62499952 a numeric vector

X4.61499977 a numeric vector
X4.60499954 a numeric vector
X4.59499979 a numeric vector
X4.58499956 a numeric vector
X4.57499981 a numeric vector
X4.56499958 a numeric vector
X4.55499983 a numeric vector
X4.5449996 a numeric vector
X4.53499985 a numeric vector
X4.52499962 a numeric vector
X4.51499987 a numeric vector
X4.50499964 a numeric vector
X4.49499989 a numeric vector
X4.48499966 a numeric vector
X4.4749999 a numeric vector
X4.46499968 a numeric vector
X4.45499992 a numeric vector
X4.44499969 a numeric vector
X4.43499947 a numeric vector
X4.42499971 a numeric vector
X4.41499949 a numeric vector
X4.40499973 a numeric vector
X4.3949995 a numeric vector
X4.38499975 a numeric vector
X4.37499952 a numeric vector
X4.36499977 a numeric vector
X4.35499954 a numeric vector
X4.34499979 a numeric vector
X4.33499956 a numeric vector
X4.32499981 a numeric vector
X4.31499958 a numeric vector
X4.30499983 a numeric vector
X4.2949996 a numeric vector
X4.28499985 a numeric vector
X4.27499962 a numeric vector
X4.26499987 a numeric vector
X4.25499964 a numeric vector

X4.24499989 a numeric vector
X4.23499966 a numeric vector
X4.22499999 a numeric vector
X4.21499968 a numeric vector
X4.20499992 a numeric vector
X4.19499969 a numeric vector
X4.18499994 a numeric vector
X4.17499971 a numeric vector
X4.16499949 a numeric vector
X4.15499973 a numeric vector
X4.1449995 a numeric vector
X4.13499975 a numeric vector
X4.12499952 a numeric vector
X4.11499977 a numeric vector
X4.10499954 a numeric vector
X4.09499979 a numeric vector
X4.08499956 a numeric vector
X4.07499981 a numeric vector
X4.06499958 a numeric vector
X4.05499983 a numeric vector
X4.0449996 a numeric vector
X4.03499985 a numeric vector
X4.02499962 a numeric vector
X4.01499987 a numeric vector
X4.00499964 a numeric vector
X3.99499965 a numeric vector
X3.98499966 a numeric vector
X3.97499967 a numeric vector
X3.96499968 a numeric vector
X3.95499969 a numeric vector
X3.94499969 a numeric vector
X3.9349997 a numeric vector
X3.92499971 a numeric vector
X3.91499972 a numeric vector
X3.90499973 a numeric vector
X3.89499974 a numeric vector
X3.88499975 a numeric vector

X3.87499976 a numeric vector
X3.86499977 a numeric vector
X3.85499978 a numeric vector
X3.84499979 a numeric vector
X3.8349998 a numeric vector
X3.82499981 a numeric vector
X3.81499982 a numeric vector
X3.80499983 a numeric vector
X3.7949996 a numeric vector
X3.78499961 a numeric vector
X3.77499962 a numeric vector
X3.76499963 a numeric vector
X3.75499964 a numeric vector
X3.74499965 a numeric vector
X3.73499966 a numeric vector
X3.72499967 a numeric vector
X3.71499968 a numeric vector
X3.70499969 a numeric vector
X3.69499969 a numeric vector
X3.6849997 a numeric vector
X3.67499971 a numeric vector
X3.66499972 a numeric vector
X3.65499973 a numeric vector
X3.64499974 a numeric vector
X3.63499975 a numeric vector
X3.62499976 a numeric vector
X3.61499977 a numeric vector
X3.60499978 a numeric vector
X3.59499979 a numeric vector
X3.5849998 a numeric vector
X3.57499981 a numeric vector
X3.56499982 a numeric vector
X3.55499983 a numeric vector
X3.54499984 a numeric vector
X3.53499961 a numeric vector
X3.52499962 a numeric vector
X3.51499963 a numeric vector

X3.50499964 a numeric vector
X3.49499965 a numeric vector
X3.48499966 a numeric vector
X3.47499967 a numeric vector
X3.46499968 a numeric vector
X3.45499969 a numeric vector
X3.44499969 a numeric vector
X3.4349997 a numeric vector
X3.42499971 a numeric vector
X3.41499972 a numeric vector
X3.40499973 a numeric vector
X3.39499974 a numeric vector
X3.38499975 a numeric vector
X3.37499976 a numeric vector
X3.36499977 a numeric vector
X3.35499978 a numeric vector
X3.34499979 a numeric vector
X3.3349998 a numeric vector
X3.32499981 a numeric vector
X3.31499982 a numeric vector
X3.30499983 a numeric vector
X3.29499984 a numeric vector
X3.28499961 a numeric vector
X3.27499962 a numeric vector
X3.26499963 a numeric vector
X3.25499964 a numeric vector
X3.24499965 a numeric vector
X3.23499966 a numeric vector
X3.22499967 a numeric vector
X3.21499968 a numeric vector
X3.20499969 a numeric vector
X3.19499969 a numeric vector
X3.1849997 a numeric vector
X3.17499971 a numeric vector
X3.16499972 a numeric vector
X3.15499973 a numeric vector
X3.14499974 a numeric vector

X3.13499975 a numeric vector
X3.12499976 a numeric vector
X3.11499977 a numeric vector
X3.10499978 a numeric vector
X3.09499979 a numeric vector
X3.0849998 a numeric vector
X3.07499981 a numeric vector
X3.06499982 a numeric vector
X3.05499983 a numeric vector
X3.04499984 a numeric vector
X3.03499985 a numeric vector
X3.02499962 a numeric vector
X3.01499963 a numeric vector
X3.00499964 a numeric vector
X2.99499965 a numeric vector
X2.98499966 a numeric vector
X2.97499967 a numeric vector
X2.96499968 a numeric vector
X2.95499969 a numeric vector
X2.94499969 a numeric vector
X2.9349997 a numeric vector
X2.92499971 a numeric vector
X2.91499972 a numeric vector

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(colon)  
str(colon)
```

ind_BCa_nt1BC	<i>ind_BCa_nt1BC</i>
---------------	----------------------

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt1BC
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt1BC)
## maybe str(ind_BCa_nt1BC) ; plot(ind_BCa_nt1BC) ...
```

ind_BCa_nt1BR	<i>ind_BCa_nt1BR</i>
---------------	----------------------

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt1BR
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt1BR)
## maybe str(ind_BCa_nt1BR) ; plot(ind_BCa_nt1BR) ...
```

ind_BCa_nt2BC

ind_BCa_nt2BC

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt2BC
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt2BC)
## maybe str(ind_BCa_nt2BC) ; plot(ind_BCa_nt2BC) ...
```

ind_BCa_nt2BR	<i>ind_BCa_nt2BR</i>
---------------	----------------------

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt2BR
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt2BR)
## maybe str(ind_BCa_nt2BR) ; plot(ind_BCa_nt2BR) ...
```

ind_BCa_nt3	<i>ind_BCa_nt3</i>
-------------	--------------------

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt3
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt3)
## maybe str(ind_BCa_nt3) ; plot(ind_BCa_nt3) ...
```

ind_BCa_nt3BC

ind_BCa_nt3BC

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt3BC
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt3BC)
## maybe str(ind_BCa_nt3BC) ; plot(ind_BCa_nt3BC) ...
```

ind_BCa_nt3BR	<i>ind_BCa_nt3BR</i>
---------------	----------------------

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt3BR
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt3BR)
## maybe str(ind_BCa_nt3BR) ; plot(ind_BCa_nt3BR) ...
```

ind_BCa_nt4BC	<i>ind_BCa_nt4BC</i>
---------------	----------------------

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt4BC
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt4BC)
## maybe str(ind_BCa_nt4BC) ; plot(ind_BCa_nt4BC) ...
```

ind_BCa_nt4BR

ind_BCa_nt4BR

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt4BR
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt4BR)
## maybe str(ind_BCa_nt4BR) ; plot(ind_BCa_nt4BR) ...
```

ind_BCa_nt5BC	<i>ind_BCa_nt5BC</i>
---------------	----------------------

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt5BC
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt5BC)
## maybe str(ind_BCa_nt5BC) ; plot(ind_BCa_nt5BC) ...
```

ind_BCa_nt5BR	<i>ind_BCa_nt5BR</i>
---------------	----------------------

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt5BR
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt5BR)
## maybe str(ind_BCa_nt5BR) ; plot(ind_BCa_nt5BR) ...
```

ind_BCa_nt6BC

ind_BCa_nt6BC

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt6BC
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt6BC)
## maybe str(ind_BCa_nt6BC) ; plot(ind_BCa_nt6BC) ...
```

ind_BCa_nt6BR	<i>ind_BCa_nt6BR</i>
---------------	----------------------

Description

Variable selection results for the vignette.

Usage

```
ind_BCa_nt6BR
```

Format

Logical vector of length 60.

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(ind_BCa_nt6BR)
## maybe str(ind_BCa_nt6BR) ; plot(ind_BCa_nt6BR) ...
```

kfolds2Chisq	<i>Computes Predicted Chisquare for kfold cross validated partial least squares beta regression models.</i>
--------------	---

Description

This function computes Predicted Chisquare for kfold cross validated partial least squares beta regression models.

Usage

```
kfolds2Chisq(pls_kfolds)
```

Arguments

pls_kfolds a kfold cross validated partial least squares regression glm model

Value

<code>list</code>	Total Predicted Chisquare vs number of components for the first group partition
<code>list()</code>	...
<code>list</code>	Total Predicted Chisquare vs number of components for the last group partition

Note

Use `PLS_beta_kfoldcv` to create kfold cross validated partial least squares regression glm and beta models.

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

`kfolds2coeff`, `kfolds2Press`, `kfolds2Pressind`, `kfolds2Chisqind`, `kfolds2Mclassifiedind` and `kfolds2Mclassified` to extract and transforms results from kfold cross validation.

Examples

```
## Not run:  
data("GasolineYield", package="betareg")  
yGasolineYield <- GasolineYield$yield  
XGasolineYield <- GasolineYield[,2:5]  
bbb <- PLS_beta_kfoldcv(yGasolineYield, XGasolineYield, nt=3, modele="pls-beta")  
kfolds2Chisq(bbb)  
  
## End(Not run)
```

kfold2Chisqind	<i>Computes individual Predicted Chisquare for kfold cross validated partial least squares beta regression models.</i>
----------------	--

Description

This function computes individual Predicted Chisquare for kfold cross validated partial least squares beta regression models.

Usage

```
kfold2Chisqind(pls_kfolds)
```

Arguments

pls_kfolds a kfold cross validated partial least squares regression glm model

Value

list Individual PChisq vs number of components for the first group partition
list() ...
list Individual PChisq vs number of components for the last group partition

Note

Use [PLS_beta_kfoldcv](#) to create kfold cross validated partial least squares regression glm models.

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[kfold2coeff](#), [kfold2Press](#), [kfold2Pressind](#), [kfold2Chisq](#), [kfold2Mclassifiedind](#) and [kfold2Mclassified](#) to extract and transforms results from kfold cross validation.

Examples

```
## Not run:
data("GasolineYield", package="betareg")
yGasolineYield <- GasolineYield$yield
XGasolineYield <- GasolineYield[,2:5]
bbb <- PLS_beta_kfoldcv(yGasolineYield, XGasolineYield, nt=3, modele="pls-beta")
kfolds2Chisqind(bbb)

## End(Not run)
```

kfolds2CVinfos_beta	<i>Extracts and computes information criteria and fits statistics for kfold cross validated partial least squares beta regression models</i>
---------------------	--

Description

This function extracts and computes information criteria and fits statistics for kfold cross validated partial least squares beta regression models for both formula or classic specifications of the model.

Usage

```
kfolds2CVinfos_beta(pls_kfolds, MClassed = FALSE)
```

Arguments

pls_kfolds	an object computed using PLS_beta_kfoldcv
MClassed	should number of miss classed be computed

Details

The Mclassed option should only set to TRUE if the response is binary.

Value

list	table of fit statistics for first group partition
list()	...
list	table of fit statistics for last group partition

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[kfolds2coeff](#), [kfolds2Pressind](#), [kfolds2Press](#), [kfolds2Mclassifiedind](#) and [kfolds2Mclassified](#) to extract and transforms results from kfold cross validation.

Examples

```
## Not run:
data("GasolineYield",package="betareg")
bbb <- PLS_beta_kfoldcv_formula(yield~.,data=GasolineYield,nt=3,modele="pls-beta")
kfolds2CVinfos_beta(bbb)

## End(Not run)
```

modpls.boot3

Bootstrap distribution of a 3 components model A precomputed bootstrap distribution of the coefficients of a model used in the vignette.

Description

Bootstrap distribution of a 3 components model

A precomputed bootstrap distribution of the coefficients of a model used in the vignette.

Usage

```
modpls.boot3
```

Format

a class boot object

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), *J. SFdS*, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). *useR!* 2021, Zurich.

Examples

```
data(modpls.boot3)
str(modpls.boot3)
plot(modpls.boot3)
```

modpls_sub4

A plsRbetamodel model on a data subset A precomputed four components plsRbetamodel fitted to a subset of an example dataset and used in the vignette.

Description

A plsRbetamodel model on a data subset

A precomputed four components plsRbetamodel fitted to a subset of an example dataset and used in the vignette.

Usage

```
modpls_sub4
```

Format

a class plsRbetamodel object

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(modpls_sub4)
str(modpls_sub4)
```

permcoefs.plsRbeta *Coefficients function for permutation bootstrap techniques*

Description

A function passed to boot to perform bootstrap.

Usage

```
permcoefs.plsRbeta(
  dataset,
  ind,
  nt,
  modele,
  family = NULL,
  method = "logistic",
  link = "logit",
  link.phi = NULL,
  type = "ML",
  verbose = TRUE
)
```

Arguments

dataset	dataset to resample
ind	indices for resampling
nt	number of components to use
modele	name of the PLS glm or PLS beta model to be fitted ("pls", "pls-glm-Gamma", "pls-glm-gaussian", "pls-glm-inverse.gaussian", "pls-glm-logistic", "pls-glm-poisson", "pls-glm-polr", "pls-beta"). Use "modele=pls-glm-family" to enable the family option.
family	family to use if GLM model, see plsRbeta
method	method for beta regression
link	link for beta regression
link.phi	link.phi for beta regression
type	type of estimates
verbose	should info messages be displayed ?

Value

Estimates on a bootstrap sample.

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

See also [bootplsbeta](#).

Examples

```
data("GasolineYield", package="betareg")

GazYield.boot <- bootplsbeta(plsRbeta(yield~., data=GasolineYield, nt=3,
modele="pls-beta", verbose=FALSE), sim="ordinary", stype="i", R=250, statistic=permcoefs.plsRbeta)
```

permcoefs.plsRbeta.raw

Raw coefficients function for permutation bootstrap techniques

Description

A function passed to boot to perform bootstrap.

Usage

```
permcoefs.plsRbeta.raw(
  dataset,
  ind,
  nt,
  modele,
  family = NULL,
  method = "logistic",
  link = "logit",
  link.phi = NULL,
  type = "ML",
  verbose = TRUE
)
```


Arguments

dataset	dataset to resample
ind	indices for resampling
nt	number of components to use
modele	name of the PLS glm or PLS beta model to be fitted ("pls", "pls-glm-Gamma", "pls-glm-gaussian", "pls-glm-inverse.gaussian", "pls-glm-logistic", "pls-glm-poisson", "pls-glm-polr", "pls-beta"). Use "modele=pls-glm-family" to enable the family option.
family	family to use if GLM model, see plsRbeta
method	method for beta regression
link	link for beta regression
link.phi	link.phi for beta regression
type	type of estimates
verbose	should info messages be displayed ?

Value

Estimates on a bootstrap sample.

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

See also [bootplsbeta](#).

Examples

```
data("GasolineYield", package="betareg")

data("GasolineYield", package="betareg")
modpls <- permcoefs.plsRbeta.raw(GasolineYield[, -6], 1:32, nt=3, modele="pls-beta")
```

permcoefs.plsRbetanp *Coefficients for permutation bootstrap computations of PLSBeta models*

Description

A function passed to boot to perform bootstrap.

Usage

```
permcoefs.plsRbetanp(  
  dataRepYtt,  
  ind,  
  nt,  
  modele,  
  family = NULL,  
  maxcoefvalues,  
  wwetoile,  
  ifbootfail  
)
```

Arguments

dataRepYtt	components' coordinates to bootstrap
ind	indices for resampling
nt	number of components to use
modele	type of modele to use, see plsRbeta
family	glm family to use, see plsRbeta
maxcoefvalues	maximum values allowed for the estimates of the coefficients to discard those coming from singular bootstrap samples
wwetoile	values of the Wstar matrix in the original fit
ifbootfail	value to return if the estimation fails on a bootstrap sample

Value

estimates on a bootstrap sample or ifbootfail value if the bootstrap computation fails.

Note

~~some notes~~

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

See Also

See also [bootplsbeta](#)

Examples

```
data("GasolineYield",package="betareg")
modplsbeta <- plsRbeta(yield~.,data=GasolineYield,nt=3, modele="pls-beta")
bootplsbeta(modplsbeta, R=250, statistic=permcoefs.plsRbetanp)
```

 plsRbeta

Partial least squares Regression beta regression models

Description

This function implements Partial least squares Regression generalized linear models complete or incomplete datasets.

Usage

```
plsRbeta(x, ...)
## Default S3 method:
plsRbetamodel(dataY,dataX,nt=2,limQ2set=.0975,
dataPredictY=dataX,modele="pls",family=NULL,typeVC="none",EstimXNA=FALSE,
scaleX=TRUE,scaleY=NULL,pvals.expli=FALSE,alpha.pvals.expli=.05,
MClassed=FALSE,tol_Xi=10^(-12),weights,method,sparse=FALSE,sparseStop=TRUE,
naive=FALSE,link=NULL,link.phi=NULL,type="ML",verbose=TRUE)
## S3 method for class 'formula'
plsRbetamodel(formula,data=NULL,nt=2,limQ2set=.0975,
dataPredictY,modele="pls",family=NULL,typeVC="none",EstimXNA=FALSE,
scaleX=TRUE,scaleY=NULL,pvals.expli=FALSE,alpha.pvals.expli=.05,
MClassed=FALSE,tol_Xi=10^(-12),weights,subset,start=NULL,etastart,
mustart,offset,method="glm.fit",control= list(),contrasts=NULL,
sparse=FALSE,sparseStop=TRUE,naive=FALSE,link=NULL,link.phi=NULL,type="ML",
verbose=TRUE)
```

Arguments

x	a formula or a response (training) dataset
dataY	response (training) dataset
dataX	predictor(s) (training) dataset
formula	an object of class " formula " (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under 'Details'.

data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>plsRbeta</code> is called.
nt	number of components to be extracted
limQ2set	limit value for the Q2
dataPredictY	predictor(s) (testing) dataset
modele	name of the PLS glm or PLS beta model to be fitted ("pls", "pls-glm-Gamma", "pls-glm-gaussian", "pls-glm-inverse.gaussian", "pls-glm-logistic", "pls-glm-poisson", "pls-glm-polr", "pls-beta"). Use "modele=pls-glm-family" to enable the family option.
family	a description of the error distribution and link function to be used in the model. This can be a character string naming a family function, a family function or the result of a call to a family function. (See <code>family</code> for details of family functions.) To use the family option, please set <code>modele="pls-glm-family"</code> . User defined families can also be defined. See details.
typeVC	type of leave one out cross validation. For back compatibility purpose. none no cross validation standard no cross validation missingdata no cross validation adaptative no cross validation
EstimXNA	only for <code>modele="pls"</code> . Set whether the missing X values have to be estimated.
scaleX	scale the predictor(s) : must be set to TRUE for <code>modele="pls"</code> and should be for glms pls.
scaleY	scale the response : Yes/No. Ignored since non always possible for glm responses.
pvals.expli	should individual p-values be reported to tune model selection ?
alpha.pvals.expli	level of significance for predictors when <code>pvals.expli=TRUE</code>
MClassed	number of missclassified cases, should only be used for binary responses
tol_Xi	minimal value for $\text{Norm}_2(X_i)$ and $\det(pp' \times pp)$ if there is any missing value in the dataX. It defaults to 10^{-12}
weights	an optional vector of 'prior weights' to be used in the fitting process. Should be NULL or a numeric vector.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
start	starting values for the parameters in the linear predictor.
etastart	starting values for the linear predictor.
mustart	starting values for the vector of means.
offset	this can be used to specify an <i>a priori</i> known component to be included in the linear predictor during fitting. This should be NULL or a numeric vector of length equal to the number of cases. One or more <code>offset</code> terms can be included in the formula instead or as well, and if more than one is specified their sum is used. See <code>model.offset</code> .

method	the method to be used in fitting the model. The default method "glm.fit" uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as glm.fit.
control	a list of parameters for controlling the fitting process. For glm.fit this is passed to glm.control.
contrasts	an optional list. See the contrasts.arg of model.matrix.default.
sparse	should the coefficients of non-significant predictors (<alpha.pvals.expli) be set to 0
sparseStop	should component extraction stop when no significant predictors (<alpha.pvals.expli) are found
naive	Use the naive estimates for the Degrees of Freedom in plsR? Default is FALSE.
link	character specification of the link function in the mean model (mu). Currently, "logit", "probit", "cloglog", "cauchit", "log", "loglog" are supported. Alternatively, an object of class "link-glm" can be supplied.
link.phi	character specification of the link function in the precision model (phi). Currently, "identity", "log", "sqrt" are supported. The default is "log" unless formula is of type y~x where the default is "identity" (for backward compatibility). Alternatively, an object of class "link-glm" can be supplied.
type	character specification of the type of estimator. Currently, maximum likelihood ("ML"), ML with bias correction ("BC"), and ML with bias reduction ("BR") are supported.
verbose	should info messages be displayed ?
...	arguments to pass to plsRmodel.default or to plsRmodel.formula

Details

There are seven different predefined models with predefined link functions available :

"pls" ordinary pls models

"pls-glm-Gamma" glm gaussian with inverse link pls models

"pls-glm-gaussian" glm gaussian with identity link pls models

"pls-glm-inverse-gamma" glm binomial with square inverse link pls models

"pls-glm-logistic" glm binomial with logit link pls models

"pls-glm-poisson" glm poisson with log link pls models

"pls-glm-polr" glm polr with logit link pls models

Using the "family=" option and setting "modele=pls-glm-family" allows changing the family and link function the same way as for the glm function. As a consequence user-specified families can also be used.

The gaussian family accepts the links (as names) identity, log and inverse.

The binomial family accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

The Gamma family accepts the links inverse, identity and log.

The poisson family accepts the links log, identity, and sqrt.

The inverse.gaussian family accepts the links $1/\mu^2$, inverse, identity and log.

The quasi family accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

The function `power` can be used to create a power link function.

A typical predictor has the form `response ~ terms` where `response` is the (numeric) response vector and `terms` is a series of terms which specifies a linear predictor for response. A terms specification of the form `first + second` indicates all the terms in `first` together with all the terms in `second` with any duplicates removed.

A specification of the form `first:second` indicates the the set of terms obtained by taking the interactions of all terms in `first` with all terms in `second`. The specification `first*second` indicates the cross of `first` and `second`. This is the same as `first + second + first:second`.

The terms in the formula will be re-ordered so that main effects come first, followed by the interactions, all second-order, all third-order and so on: to avoid this pass a terms object as the formula.

Non-NULL weights can be used to indicate that different observations have different dispersions (with the values in weights being inversely proportional to the dispersions); or equivalently, when the elements of weights are positive integers w_i , that each response y_i is the mean of w_i unit-weight observations.

The default estimator for Degrees of Freedom is the Kramer and Sugiyama's one which only works for classical plsR models. For these models, Information criteria are computed accordingly to these estimations. Naive Degrees of Freedom and Information Criteria are also provided for comparison purposes. For more details, see Kraemer, N., Sugiyama M. (2010). "The Degrees of Freedom of Partial Least Squares Regression". preprint, <http://arxiv.org/abs/1002.4112>.

Value

Depends on the model that was used to fit the model.

Note

Use `plsRbeta` instead.

Author(s)

Frédéric Bertrand
 <frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFds/article/view/215>

See Also[plsR](#) and [plsRglm](#)**Examples**

```
data("GasolineYield",package="betareg")
modpls <- plsRbeta(yield~.,data=GasolineYield,nt=3,modele="pls-beta")
modpls$pp
modpls$Coeffs
modpls$Std.Coeffs
modpls$InfCrit
modpls$PredictY[1,]
rm("modpls")

data("GasolineYield",package="betareg")
yGasolineYield <- GasolineYield$yield
XGasolineYield <- GasolineYield[,2:5]
modpls <- plsRbeta(yGasolineYield,XGasolineYield,nt=3,modele="pls-beta")
modpls$pp
modpls$Coeffs
modpls$Std.Coeffs
modpls$InfCrit
modpls$PredictY[1,]
rm("modpls")
```

PLS_beta

Partial least squares beta regression models

Description

This function implements Partial least squares beta regression models on complete or incomplete datasets.

Usage

```
PLS_beta(  
  dataY,  
  dataX,  
  nt = 2,  
  limQ2set = 0.0975,  
  dataPredictY = dataX,  
  modele = "pls",  
  family = NULL,  
  typeVC = "none",  
  EstimXNA = FALSE,  
  scaleX = TRUE,
```

```

scaleY = NULL,
pvals.expli = FALSE,
alpha.pvals.expli = 0.05,
MClassed = FALSE,
tol_Xi = 10^(-12),
weights,
method,
sparse = FALSE,
sparseStop = TRUE,
naive = FALSE,
link = NULL,
link.phi = NULL,
type = "ML",
verbose = TRUE
)

```

Arguments

dataY	response (training) dataset
dataX	predictor(s) (training) dataset
nt	number of components to be extracted
limQ2set	limit value for the Q2
dataPredictY	predictor(s) (testing) dataset
modele	name of the PLS glm or PLS beta model to be fitted ("pls", "pls-glm-Gamma", "pls-glm-gaussian", "pls-glm-inverse.gaussian", "pls-glm-logistic", "pls-glm-poisson", "pls-glm-polr", "pls-beta"). Use "modele=pls-glm-family" to enable the family option.
family	a description of the error distribution and link function to be used in the model. This can be a character string naming a family function, a family function or the result of a call to a family function. (See family for details of family functions.) To use the family option, please set modele="pls-glm-family". User defined families can also be defined. See details.
typeVC	type of leave one out cross validation. For back compatibility purpose. list("none") no cross validation list("standard") no cross validation list("missingdata") no cross validation list("adaptative") no cross validation
EstimXNA	only for modele="pls". Set whether the missing X values have to be estimated.
scaleX	scale the predictor(s) : must be set to TRUE for modele="pls" and should be for glms pls.
scaleY	scale the response : Yes/No. Ignored since not always possible for glm responses.
pvals.expli	should individual p-values be reported to tune model selection ?
alpha.pvals.expli	level of significance for predictors when pvals.expli=TRUE

MClassed	number of missclassified cases, should only be used for binary responses
tol_Xi	minimal value for Norm2(Xi) and $\det(pp' \times pp)$ if there is any missing value in the dataX. It defaults to 10^{-12}
weights	an optional vector of 'prior weights' to be used in the fitting process. Should be NULL or a numeric vector.
method	the link function for pls-glm-polr, logistic, probit, complementary log-log or cauchit (corresponding to a Cauchy latent variable).
sparse	should the coefficients of non-significant predictors (<alpha.pvals.expli) be set to 0
sparseStop	should component extraction stop when no significant predictors (<alpha.pvals.expli) are found
naive	use the naive estimates for the Degrees of Freedom in plsR? Default is FALSE.
link	character specification of the link function in the mean model (mu). Currently, "logit", "probit", "cloglog", "cauchit", "log", "loglog" are supported. Alternatively, an object of class "link-glm" can be supplied.
link.phi	character specification of the link function in the precision model (phi). Currently, "identity", "log", "sqrt" are supported. The default is "log" unless formula is of type $y \sim x$ where the default is "identity" (for backward compatibility). Alternatively, an object of class "link-glm" can be supplied.
type	character specification of the type of estimator. Currently, maximum likelihood ("ML"), ML with bias correction ("BC"), and ML with bias reduction ("BR") are supported.
verbose	should info messages be displayed ?

Details

There are seven different predefined models with predefined link functions available :

list("\pls\") ordinary pls models

list("\pls-glm-Gamma\") glm gaussian with inverse link pls models

list("\pls-glm-gaussian\") glm gaussian with identity link pls models

list("\pls-glm-inverse-gamma\") glm binomial with square inverse link pls models

list("\pls-glm-logistic\") glm binomial with logit link pls models

list("\pls-glm-poisson\") glm poisson with log link pls models

list("\pls-glm-polr\") glm polr with logit link pls models

Using the "family=" option and setting "modele=pls-glm-family" allows changing the family and link function the same way as for the `glm` function. As a consequence user-specified families can also be used.

The accepts the links (as names) identity, log and inverse.

list("gaussian") accepts the links (as names) identity, log and inverse.

family accepts the links (as names) identity, log and inverse.

The accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

list("binomial") accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

family accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

The accepts the links inverse, identity and log.

list("Gamma") accepts the links inverse, identity and log.

family accepts the links inverse, identity and log.

The accepts the links log, identity, and sqrt.

list("poisson") accepts the links log, identity, and sqrt.

family accepts the links log, identity, and sqrt.

The accepts the links $1/\mu^2$, inverse, identity and log.

list("inverse.gaussian") accepts the links $1/\mu^2$, inverse, identity and log.

family accepts the links $1/\mu^2$, inverse, identity and log.

The accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

list("quasi") accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

family accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

The function can be used to create a power link function.

list("power") can be used to create a power link function.

The default estimator for Degrees of Freedom is the Kramer and Sugiyama's one which only works for classical plsR models. For these models, Information criteria are computed accordingly to these estimations. Naive Degrees of Freedom and Information Criteria are also provided for comparison purposes. For more details, see Kraemer, N., Sugiyama M. (2010). "The Degrees of Freedom of Partial Least Squares Regression". preprint, <http://arxiv.org/abs/1002.4112>.

Value

Depends on the model that was used to fit the model.

Note

Use `plsRbeta` instead.

Author(s)

Frédéric Bertrand
 <frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[PLS_beta_wvc](#) and [PLS_beta_kfoldcv](#)

Examples

```
data("GasolineYield",package="betareg")
yGasolineYield <- GasolineYield$yield
XGasolineYield <- GasolineYield[,2:5]
modpls <- PLS_beta(yGasolineYield,XGasolineYield,nt=3,modele="pls-beta")
modpls$pp
modpls$Coeffs
modpls$Std.Coeffs
modpls$InfCrit
modpls$PredictY[1,]
rm("modpls")
```

PLS_beta_formula

Partial least squares beta regression models

Description

This function implements Partial least squares beta regression models on complete or incomplete datasets (formula specification of the model).

Usage

```
PLS_beta_formula(
  formula,
  data = NULL,
  nt = 2,
  limQ2set = 0.0975,
  dataPredictY = dataX,
  modele = "pls",
  family = NULL,
  typeVC = "none",
  EstimXNA = FALSE,
  scaleX = TRUE,
```

```

scaleY = NULL,
pvals.expli = FALSE,
alpha.pvals.expli = 0.05,
MClassed = FALSE,
tol_Xi = 10^(-12),
weights,
subset,
start = NULL,
etastart,
mustart,
offset,
method,
control = list(),
contrasts = NULL,
sparse = FALSE,
sparseStop = TRUE,
naive = FALSE,
link = NULL,
link.phi = NULL,
type = "ML",
verbose = TRUE
)

```

Arguments

formula	an object of class " <code>formula</code> " (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under 'Details'.
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>plsRbeta</code> is called.
nt	number of components to be extracted
limQ2set	limit value for the Q2
dataPredictY	predictor(s) (testing) dataset
modele	name of the PLS glm or PLS beta model to be fitted (" <code>pls</code> ", " <code>pls-glm-Gamma</code> ", " <code>pls-glm-gaussian</code> ", " <code>pls-glm-inverse.gaussian</code> ", " <code>pls-glm-logistic</code> ", " <code>pls-glm-poisson</code> ", " <code>pls-glm-polr</code> ", " <code>pls-beta</code> "). Use " <code>modele=pls-glm-family</code> " to enable the family option.
family	a description of the error distribution and link function to be used in the model. This can be a character string naming a family function, a family function or the result of a call to a family function. (See <code>family</code> for details of family functions.) To use the family option, please set <code>modele="pls-glm-family"</code> . User defined families can also be defined. See details.
typeVC	type of leave one out cross validation. For back compatibility purpose. list("none") no cross validation

	list("standard") no cross validation
	list("missingdata") no cross validation
	list("adaptative") no cross validation
EstimXNA	only for modele="pls". Set whether the missing X values have to be estimated.
scaleX	scale the predictor(s) : must be set to TRUE for modele="pls" and should be for glms pls.
scaleY	scale the response : Yes/No. Ignored since not always possible for glm responses.
pvals.expli	should individual p-values be reported to tune model selection ?
alpha.pvals.expli	level of significance for predictors when pvals.expli=TRUE
MClassed	number of missclassified cases, should only be used for binary responses
tol_Xi	minimal value for Norm2(Xi) and $\det(pp' \times pp)$ if there is any missing value in the dataX. It defaults to 10^{-12}
weights	an optional vector of 'prior weights' to be used in the fitting process. Should be NULL or a numeric vector.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
start	starting values for the parameters in the linear predictor.
etastart	starting values for the linear predictor.
mustart	starting values for the vector of means.
offset	this can be used to specify an <i>a priori</i> known component to be included in the linear predictor during fitting. This should be NULL or a numeric vector of length equal to the number of cases. One or more offset terms can be included in the formula instead or as well, and if more than one is specified their sum is used. See model.offset .
method	<p>for fitting glms with glm (the method to be used in fitting the model. The default method "glm.fit" uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as glm.fit. If "model.frame", the model frame is returned.</p> <p>list("\pls-glm-Gamma\") the method to be used in fitting the model. The default method "glm.fit" uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as glm.fit. If "model.frame", the model frame is returned.</p> <p>, the method to be used in fitting the model. The default method "glm.fit" uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as glm.fit. If "model.frame", the model frame is returned.</p> <p>list("\pls-glm-gaussian\") the method to be used in fitting the model. The default method "glm.fit" uses iteratively reweighted least squares (IWLS).</p>

- User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
- , the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
 - `list("\pls-glm-inverse.gaussian\")`** the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
 - , the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
 - `list("\pls-glm-logistic\")`** the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
 - , the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
 - `list("\pls-glm-poisson\")`** the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
 - , the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
 - `list("\modele=pls-glm-family\")`** the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
 -) the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a

	function, with a function which takes the same arguments as <code>glm.fit</code> . If "model.frame", the model frame is returned.
	list("pls-glm-polr") logistic, probit, complementary log-log or cauchit (corresponding to a Cauchy latent variable).
control	a list of parameters for controlling the fitting process. For <code>glm.fit</code> this is passed to <code>glm.control</code> .
contrasts	an optional list. See the <code>contrasts.arg</code> of <code>model.matrix.default</code> .
sparse	should the coefficients of non-significant predictors (<code><alpha.pvals.expli</code>) be set to 0
sparseStop	should component extraction stop when no significant predictors (<code><alpha.pvals.expli</code>) are found
naive	Use the naive estimates for the Degrees of Freedom in plsR? Default is FALSE.
link	character specification of the link function in the mean model (μ). Currently, "logit", "probit", "cloglog", "cauchit", "log", "loglog" are supported. Alternatively, an object of class "link-glm" can be supplied.
link.phi	character specification of the link function in the precision model (ϕ). Currently, "identity", "log", "sqrt" are supported. The default is "log" unless formula is of type $y \sim x$ where the default is "identity" (for backward compatibility). Alternatively, an object of class "link-glm" can be supplied.
type	character specification of the type of estimator. Currently, maximum likelihood ("ML"), ML with bias correction ("BC"), and ML with bias reduction ("BR") are supported.
verbose	should info messages be displayed ?

Details

There are seven different predefined models with predefined link functions available :

list("\pls\") ordinary pls models

list("\pls-glm-Gamma\") glm gaussian with inverse link pls models

list("\pls-glm-gaussian\") glm gaussian with identity link pls models

list("\pls-glm-inverse-gamma\") glm binomial with square inverse link pls models

list("\pls-glm-logistic\") glm binomial with logit link pls models

list("\pls-glm-poisson\") glm poisson with log link pls models

list("\pls-glm-polr\") glm polr with logit link pls models

Using the "family=" option and setting "modele=pls-glm-family" allows changing the family and link function the same way as for the `glm` function. As a consequence user-specified families can also be used.

The accepts the links (as names) identity, log and inverse.

list("gaussian") accepts the links (as names) identity, log and inverse.

family accepts the links (as names) identity, log and inverse.

The accepts the links `logit`, `probit`, `cauchit`, (corresponding to logistic, normal and Cauchy CDFs respectively) `log` and `cloglog` (complementary log-log).

list("binomial") accepts the links `logit`, `probit`, `cauchit`, (corresponding to logistic, normal and Cauchy CDFs respectively) `log` and `cloglog` (complementary log-log).

family accepts the links `logit`, `probit`, `cauchit`, (corresponding to logistic, normal and Cauchy CDFs respectively) `log` and `cloglog` (complementary log-log).

The accepts the links `inverse`, `identity` and `log`.

list("Gamma") accepts the links `inverse`, `identity` and `log`.

family accepts the links `inverse`, `identity` and `log`.

The accepts the links `log`, `identity`, and `sqrt`.

list("poisson") accepts the links `log`, `identity`, and `sqrt`.

family accepts the links `log`, `identity`, and `sqrt`.

The accepts the links `1/mu^2`, `inverse`, `identity` and `log`.

list("inverse.gaussian") accepts the links `1/mu^2`, `inverse`, `identity` and `log`.

family accepts the links `1/mu^2`, `inverse`, `identity` and `log`.

The accepts the links `logit`, `probit`, `cloglog`, `identity`, `inverse`, `log`, `1/mu^2` and `sqrt`.

list("quasi") accepts the links `logit`, `probit`, `cloglog`, `identity`, `inverse`, `log`, `1/mu^2` and `sqrt`.

family accepts the links `logit`, `probit`, `cloglog`, `identity`, `inverse`, `log`, `1/mu^2` and `sqrt`.

The function can be used to create a power link function.

list("power") can be used to create a power link function.

A typical predictor has the form `response ~ terms` where `response` is the (numeric) response vector and `terms` is a series of terms which specifies a linear predictor for response. A terms specification of the form `first + second` indicates all the terms in `first` together with all the terms in `second` with any duplicates removed.

A specification of the form `first:second` indicates the the set of terms obtained by taking the interactions of all terms in `first` with all terms in `second`. The specification `first*second` indicates the cross of `first` and `second`. This is the same as `first + second + first:second`.

The terms in the formula will be re-ordered so that main effects come first, followed by the interactions, all second-order, all third-order and so on: to avoid this pass a terms object as the formula.

Non-NULL weights can be used to indicate that different observations have different dispersions (with the values in `weights` being inversely proportional to the dispersions); or equivalently, when the elements of `weights` are positive integers w_i , that each response y_i is the mean of w_i unit-weight observations.

The default estimator for Degrees of Freedom is the Kramer and Sugiyama's one which only works for classical plsR models. For these models, Information criteria are computed accordingly to these estimations. Naive Degrees of Freedom and Information Criteria are also provided for comparison purposes. For more details, see Kraemer, N., Sugiyama M. (2010). "The Degrees of Freedom of Partial Least Squares Regression". preprint, <http://arxiv.org/abs/1002.4112>.

Value

Depends on the model that was used to fit the model.

Note

Use plsRbeta instead.

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[PLS_beta_wvc](#) and [PLS_beta_kfoldcv_formula](#)

Examples

```
data("GasolineYield", package="betareg")
modpls <- PLS_beta_formula(yield~., data=GasolineYield, nt=3, modele="pls-beta")
modpls$pp
modpls$Coeffs
modpls$Std.Coeffs
modpls$InfCrit
modpls$PredictY[1,]
rm("modpls")
```

PLS_beta_kfoldcv	<i>Partial least squares regression beta models with kfold cross validation</i>
------------------	---

Description

This function implements kfold cross validation on complete or incomplete datasets for partial least squares beta regression models

Usage

```

PLS_beta_kfoldcv(
  dataY,
  dataX,
  nt = 2,
  limQ2set = 0.0975,
  modele = "pls",
  family = NULL,
  K = nrow(dataX),
  NK = 1,
  grouplist = NULL,
  random = FALSE,
  scaleX = TRUE,
  scaleY = NULL,
  keepcoeffs = FALSE,
  keepfolds = FALSE,
  keepdataY = TRUE,
  keepMclassified = FALSE,
  tol_Xi = 10^(-12),
  weights,
  method,
  link = NULL,
  link.phi = NULL,
  type = "ML",
  verbose = TRUE
)

```

Arguments

dataY	response (training) dataset
dataX	predictor(s) (training) dataset
nt	number of components to be extracted
limQ2set	limit value for the Q2
modele	name of the PLS glm or PLS beta model to be fitted ("pls", "pls-glm-Gamma", "pls-glm-gaussian", "pls-glm-inverse.gaussian", "pls-glm-logistic", "pls-glm-poisson", "pls-glm-polr", "pls-beta"). Use "modele=pls-glm-family" to enable the family option.
family	a description of the error distribution and link function to be used in the model. This can be a character string naming a family function, a family function or the result of a call to a family function. (See family for details of family functions.) To use the family option, please set modele="pls-glm-family". User defined families can also be defined. See details.
K	number of groups
NK	number of times the group division is made
grouplist	to specify the members of the K groups
random	should the K groups be made randomly

scaleX	scale the predictor(s) : must be set to TRUE for modele="pls" and should be for glms pls.
scaleY	scale the response : Yes/No. Ignored since non always possible for glm responses.
keepcoeffs	shall the coefficients for each model be returned
keepfolds	shall the groups' composition be returned
keepdataY	shall the observed value of the response for each one of the predicted value be returned
keepMclassified	shall the number of miss classed be returned (unavailable)
tol_Xi	minimal value for Norm2(Xi) and $\det(pp' \times pp)$ if there is any missing value in the dataX. It defaults to 10^{-12}
weights	an optional vector of 'prior weights' to be used in the fitting process. Should be NULL or a numeric vector.
method	logistic, probit, complementary log-log or cauchit (corresponding to a Cauchy latent variable).
link	character specification of the link function in the mean model (mu). Currently, "logit", "probit", "cloglog", "cauchit", "log", "loglog" are supported. Alternatively, an object of class "link-glm" can be supplied.
link.phi	character specification of the link function in the precision model (phi). Currently, "identity", "log", "sqrt" are supported. The default is "log" unless formula is of type $y \sim x$ where the default is "identity" (for backward compatibility). Alternatively, an object of class "link-glm" can be supplied.
type	character specification of the type of estimator. Currently, maximum likelihood ("ML"), ML with bias correction ("BC"), and ML with bias reduction ("BR") are supported.
verbose	should info messages be displayed ?

Details

Predicts 1 group with the K-1 other groups. Leave one out cross validation is thus obtained for $K = \text{nrow}(\text{dataX})$.

There are seven different predefined models with predefined link functions available :

list("\pls\") ordinary pls models

list("\pls-glm-Gamma\") glm gaussian with inverse link pls models

list("\pls-glm-gaussian\") glm gaussian with identity link pls models

list("\pls-glm-inverse-gamma\") glm binomial with square inverse link pls models

list("\pls-glm-logistic\") glm binomial with logit link pls models

list("\pls-glm-poisson\") glm poisson with log link pls models

list("\pls-glm-polr\") glm polr with logit link pls models

Using the "family=" option and setting "modele=pls-glm-family" allows changing the family and link function the same way as for the `glm` function. As a consequence user-specified families can also be used.

The accepts the links (as names) identity, log and inverse.

list("gaussian") accepts the links (as names) identity, log and inverse.

family accepts the links (as names) identity, log and inverse.

The accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

list("binomial") accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

family accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

The accepts the links inverse, identity and log.

list("Gamma") accepts the links inverse, identity and log.

family accepts the links inverse, identity and log.

The accepts the links log, identity, and sqrt.

list("poisson") accepts the links log, identity, and sqrt.

family accepts the links log, identity, and sqrt.

The accepts the links $1/\mu^2$, inverse, identity and log.

list("inverse.gaussian") accepts the links $1/\mu^2$, inverse, identity and log.

family accepts the links $1/\mu^2$, inverse, identity and log.

The accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

list("quasi") accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

family accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

The function can be used to create a power link function.

list("power") can be used to create a power link function.

Non-NULL weights can be used to indicate that different observations have different dispersions (with the values in weights being inversely proportional to the dispersions); or equivalently, when the elements of weights are positive integers w_i , that each response y_i is the mean of w_i unit-weight observations.

Value

results_kfolds list of NK. Each element of the list sums up the results for a group division:
list of K matrices of size about $nrow(\text{dataX})/K * nt$ with the predicted values for a growing number of components
list() ...
list of K matrices of size about $nrow(\text{dataX})/K * nt$ with the predicted values for a growing number of components

folds list of NK. Each element of the list sums up the informations for a group division:
list of K vectors of length about $nrow(\text{dataX})$ with the numbers of the rows of **dataX** that were used as a training set
list() ...

	list of K vectors of length about $nrow(dataX)$ with the numbers of the rows of $dataX$ that were used as a training set
<code>dataY_kfolds</code>	list of NK. Each element of the list sums up the results for a group division: list of K matrices of size about $nrow(dataX)/K * 1$ with the observed values of the response list() ... list of K matrices of size about $nrow(dataX)/K * 1$ with the observed values of the response
<code>call</code>	the call of the function

Note

Works for complete and incomplete datasets.

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[kfolds2coeff](#), [kfolds2Pressind](#), [kfolds2Press](#), [kfolds2Mclassifiedind](#), [kfolds2Mclassified](#) and [kfolds2CVinfos_beta](#) to extract and transform results from kfold cross validation.

Examples

```
## Not run:
data("GasolineYield", package="betareg")
yGasolineYield <- GasolineYield$yield
XGasolineYield <- GasolineYield[,2:5]
bbb <- PLS_beta_kfoldcv(yGasolineYield, XGasolineYield, nt=3, modele="pls-beta")
kfolds2CVinfos_beta(bbb)

## End(Not run)
```

PLS_beta_kfoldcv_formula

Partial least squares regression beta models with kfold cross validation

Description

This function implements kfold cross validation on complete or incomplete datasets for partial least squares beta regression models (formula specification of the model).

Usage

```
PLS_beta_kfoldcv_formula(  
  formula,  
  data = NULL,  
  nt = 2,  
  limQ2set = 0.0975,  
  modele = "pls",  
  family = NULL,  
  K = nrow(dataX),  
  NK = 1,  
  grouplist = NULL,  
  random = FALSE,  
  scaleX = TRUE,  
  scaleY = NULL,  
  keepcoeffs = FALSE,  
  keepfolds = FALSE,  
  keepdataY = TRUE,  
  keepMclassified = FALSE,  
  tol_xi = 10^(-12),  
  weights,  
  subset,  
  start = NULL,  
  etastart,  
  mustart,  
  offset,  
  method,  
  control = list(),  
  contrasts = NULL,  
  sparse = FALSE,  
  sparseStop = TRUE,  
  naive = FALSE,  
  link = NULL,  
  link.phi = NULL,  
  type = "ML",  
  verbose = TRUE  
)
```

Arguments

formula	an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under 'Details'.
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>plsRglm</code> is called.
nt	number of components to be extracted
limQ2set	limit value for the Q2
modele	name of the PLS glm or PLS beta model to be fitted ("pls", "pls-glm-Gamma", "pls-glm-gaussian", "pls-glm-inverse.gaussian", "pls-glm-logistic", "pls-glm-poisson", "pls-glm-polr", "pls-beta"). Use "modele=pls-glm-family" to enable the family option.
family	a description of the error distribution and link function to be used in the model. This can be a character string naming a family function, a family function or the result of a call to a family function. (See <code>family</code> for details of family functions.) To use the family option, please set <code>modele="pls-glm-family"</code> . User defined families can also be defined. See details.
K	number of groups
NK	number of times the group division is made
grouplist	to specify the members of the K groups
random	should the K groups be made randomly
scaleX	scale the predictor(s) : must be set to TRUE for <code>modele="pls"</code> and should be for glms pls.
scaleY	scale the response : Yes/No. Ignored since non always possible for glm responses.
keepcoeffs	shall the coefficients for each model be returned
keepfolds	shall the groups' composition be returned
keepdataY	shall the observed value of the response for each one of the predicted value be returned
keepMclassed	shall the number of miss classed be returned (unavailable)
tol_Xi	minimal value for $\text{Norm2}(X_i)$ and $\det(pp' \times pp)$ if there is any missing value in the dataX. It defaults to 10^{-12}
weights	an optional vector of 'prior weights' to be used in the fitting process. Should be NULL or a numeric vector.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
start	starting values for the parameters in the linear predictor.
etastart	starting values for the linear predictor.
mustart	starting values for the vector of means.

- offset this can be used to specify an *a priori* known component to be included in the linear predictor during fitting. This should be NULL or a numeric vector of length equal to the number of cases. One or more `offset` terms can be included in the formula instead or as well, and if more than one is specified their sum is used. See `model.offset`.
- method **for fitting glms with glm** (the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
- list("\pls-glm-Gamma\")** the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
- , the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
- list("\pls-glm-gaussian\")** the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
- , the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
- list("\pls-glm-inverse.gaussian\")** the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
- , the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
- list("\pls-glm-logistic\")** the method to be used in fitting the model. The default method `"glm.fit"` uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If `"model.frame"`, the model frame is returned.
- , the method to be used in fitting the model. The default method `"glm.fit"`

uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If "model.frame", the model frame is returned.

list("\pls-glm-poisson") the method to be used in fitting the model. The default method "glm.fit" uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If "model.frame", the model frame is returned.

, the method to be used in fitting the model. The default method "glm.fit" uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If "model.frame", the model frame is returned.

list("\modele=pls-glm-family") the method to be used in fitting the model. The default method "glm.fit" uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If "model.frame", the model frame is returned.

) the method to be used in fitting the model. The default method "glm.fit" uses iteratively reweighted least squares (IWLS). User-supplied fitting functions can be supplied either as a function or a character string naming a function, with a function which takes the same arguments as `glm.fit`. If "model.frame", the model frame is returned.

list("pls-glm-polr") logistic, probit, complementary log-log or cauchit (corresponding to a Cauchy latent variable).

control	a list of parameters for controlling the fitting process. For <code>glm.fit</code> this is passed to <code>glm.control</code> .
contrasts	an optional list. See the <code>contrasts.arg</code> of <code>model.matrix.default</code> .
sparse	should the coefficients of non-significant predictors (<code><alpha.pvals.expli</code>) be set to 0
sparseStop	should component extraction stop when no significant predictors (<code><alpha.pvals.expli</code>) are found
naive	Use the naive estimates for the Degrees of Freedom in plsR? Default is FALSE.
link	character specification of the link function in the mean model (μ). Currently, "logit", "probit", "cloglog", "cauchit", "log", "loglog" are supported. Alternatively, an object of class "link-glm" can be supplied.
link.phi	character specification of the link function in the precision model (ϕ). Currently, "identity", "log", "sqrt" are supported. The default is "log" unless formula is of type $y \sim x$ where the default is "identity" (for backward compatibility). Alternatively, an object of class "link-glm" can be supplied.
type	character specification of the type of estimator. Currently, maximum likelihood ("ML"), ML with bias correction ("BC"), and ML with bias reduction ("BR") are supported.
verbose	should info messages be displayed ?

Details

Predicts 1 group with the K-1 other groups. Leave one out cross validation is thus obtained for $K = \text{nrow}(\text{dataX})$.

There are seven different predefined models with predefined link functions available :

list("\pls\") ordinary pls models

list("\pls-glm-Gamma\") glm gaussian with inverse link pls models

list("\pls-glm-gaussian\") glm gaussian with identity link pls models

list("\pls-glm-inverse-gamma\") glm binomial with square inverse link pls models

list("\pls-glm-logistic\") glm binomial with logit link pls models

list("\pls-glm-poisson\") glm poisson with log link pls models

list("\pls-glm-polr\") glm polr with logit link pls models

Using the "family=" option and setting "modele=pls-glm-family" allows changing the family and link function the same way as for the `glm` function. As a consequence user-specified families can also be used.

The accepts the links (as names) identity, log and inverse.

list("gaussian") accepts the links (as names) identity, log and inverse.

family accepts the links (as names) identity, log and inverse.

The accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

list("binomial") accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

family accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

The accepts the links inverse, identity and log.

list("Gamma") accepts the links inverse, identity and log.

family accepts the links inverse, identity and log.

The accepts the links log, identity, and sqrt.

list("poisson") accepts the links log, identity, and sqrt.

family accepts the links log, identity, and sqrt.

The accepts the links $1/\mu^2$, inverse, identity and log.

list("inverse.gaussian") accepts the links $1/\mu^2$, inverse, identity and log.

family accepts the links $1/\mu^2$, inverse, identity and log.

The accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

list("quasi") accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

family accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

The function can be used to create a power link function.

list("power") can be used to create a power link function.

A typical predictor has the form `response ~ terms` where `response` is the (numeric) response vector and `terms` is a series of terms which specifies a linear predictor for response. A terms specification of the form `first + second` indicates all the terms in `first` together with all the terms in `second` with any duplicates removed.

A specification of the form `first:second` indicates the the set of terms obtained by taking the interactions of all terms in `first` with all terms in `second`. The specification `first*second` indicates the cross of `first` and `second`. This is the same as `first + second + first:second`.

The terms in the formula will be re-ordered so that main effects come first, followed by the interactions, all second-order, all third-order and so on: to avoid this pass a terms object as the formula.

Non-NULL weights can be used to indicate that different observations have different dispersions (with the values in weights being inversely proportional to the dispersions); or equivalently, when the elements of weights are positive integers w_i , that each response y_i is the mean of w_i unit-weight observations.

Value

<code>results_kfolds</code>	list of NK. Each element of the list sums up the results for a group division: list of K matrices of size about $nrow(dataX)/K * nt$ with the predicted values for a growing number of components list() ... list of K matrices of size about $nrow(dataX)/K * nt$ with the predicted values for a growing number of components
<code>folds</code>	list of NK. Each element of the list sums up the informations for a group division: list of K vectors of length about $nrow(dataX)$ with the numbers of the rows of <code>dataX</code> that were used as a training set list() ... list of K vectors of length about $nrow(dataX)$ with the numbers of the rows of <code>dataX</code> that were used as a training set
<code>dataY_kfolds</code>	list of NK. Each element of the list sums up the results for a group division: list of K matrices of size about $nrow(dataX)/K * 1$ with the observed values of the response list() ... list of K matrices of size about $nrow(dataX)/K * 1$ with the observed values of the response
<code>call</code>	the call of the function

Note

Work for complete and incomplete datasets.

Author(s)

Frédéric Bertrand
 <frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[kfolds2coeff](#), [kfolds2Pressind](#), [kfolds2Press](#), [kfolds2Mclassifiedind](#), [kfolds2Mclassified](#) and [kfolds2CVinfos_beta](#) to extract and transform results from kfold cross validation.

Examples

```
## Not run:
data("GasolineYield",package="betareg")
bbb <- PLS_beta_kfoldcv_formula(yield~.,data=GasolineYield,nt=3,modele="pls-beta")
kfolds2CVinfos_beta(bbb)

## End(Not run)
```

PLS_beta_wvc

Light version of PLS_beta for cross validation purposes

Description

Light version of PLS_beta for cross validation purposes either on complete or incomplete datasets.

Usage

```
PLS_beta_wvc(
  dataY,
  dataX,
  nt = 2,
  dataPredictY = dataX,
  modele = "pls",
  family = NULL,
  scaleX = TRUE,
  scaleY = NULL,
  keepcoeffs = FALSE,
  keepstd.coeffs = FALSE,
  tol_xi = 10-12,
  weights,
  method = "logistic",
  link = NULL,
  link.phi = NULL,
```

```

    type = "ML",
    verbose = TRUE
  )

```

Arguments

dataY	response (training) dataset
dataX	predictor(s) (training) dataset
nt	number of components to be extracted
dataPredictY	predictor(s) (testing) dataset
modele	name of the PLS glm or PLS beta model to be fitted ("pls", "pls-glm-Gamma", "pls-glm-gaussian", "pls-glm-inverse.gaussian", "pls-glm-logistic", "pls-glm-poisson", "pls-glm-polr", "pls-beta"). Use "modele=pls-glm-family" to enable the family option.
family	a description of the error distribution and link function to be used in the model. This can be a character string naming a family function, a family function or the result of a call to a family function. (See family for details of family functions.) To use the family option, please set modele="pls-glm-family". User defined families can also be defined. See details.
scaleX	scale the predictor(s) : must be set to TRUE for modele="pls" and should be for glms pls.
scaleY	scale the response : Yes/No. Ignored since non always possible for glm responses.
keepcoeffs	whether the coefficients of the linear fit on link scale of unstandardized eXplanatory variables should be returned or not.
keepstd.coeffs	whether the coefficients of the linear fit on link scale of standardized eXplanatory variables should be returned or not.
tol_Xi	minimal value for Norm2(Xi) and $\det(pp' \times pp)$ if there is any missing value in the dataX. It defaults to 10^{-12}
weights	an optional vector of 'prior weights' to be used in the fitting process. Should be NULL or a numeric vector.
method	logistic, probit, complementary log-log or cauchit (corresponding to a Cauchy latent variable).
link	character specification of the link function in the mean model (mu). Currently, "logit", "probit", "cloglog", "cauchit", "log", "loglog" are supported. Alternatively, an object of class "link-glm" can be supplied.
link.phi	character specification of the link function in the precision model (phi). Currently, "identity", "log", "sqrt" are supported. The default is "log" unless formula is of type $y \sim x$ where the default is "identity" (for backward compatibility). Alternatively, an object of class "link-glm" can be supplied.
type	character specification of the type of estimator. Currently, maximum likelihood ("ML"), ML with bias correction ("BC"), and ML with bias reduction ("BR") are supported.
verbose	should info messages be displayed ?

Details

This function is called by [PLS_glm_kfoldcv_formula](#) in order to perform cross validation either on complete or incomplete datasets.

There are seven different predefined models with predefined link functions available :

list("\pls\") ordinary pls models

list("\pls-glm-Gamma\") glm gaussian with inverse link pls models

list("\pls-glm-gaussian\") glm gaussian with identity link pls models

list("\pls-glm-inverse-gamma\") glm binomial with square inverse link pls models

list("\pls-glm-logistic\") glm binomial with logit link pls models

list("\pls-glm-poisson\") glm poisson with log link pls models

list("\pls-glm-polr\") glm polr with logit link pls models

Using the "family=" option and setting "modele=pls-glm-family" allows changing the family and link function the same way as for the [glm](#) function. As a consequence user-specified families can also be used.

The accepts the links (as names) identity, log and inverse.

list("gaussian") accepts the links (as names) identity, log and inverse.

family accepts the links (as names) identity, log and inverse.

The accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

list("binomial") accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

family accepts the links logit, probit, cauchit, (corresponding to logistic, normal and Cauchy CDFs respectively) log and cloglog (complementary log-log).

The accepts the links inverse, identity and log.

list("Gamma") accepts the links inverse, identity and log.

family accepts the links inverse, identity and log.

The accepts the links log, identity, and sqrt.

list("poisson") accepts the links log, identity, and sqrt.

family accepts the links log, identity, and sqrt.

The accepts the links $1/\mu^2$, inverse, identity and log.

list("inverse.gaussian") accepts the links $1/\mu^2$, inverse, identity and log.

family accepts the links $1/\mu^2$, inverse, identity and log.

The accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

list("quasi") accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

family accepts the links logit, probit, cloglog, identity, inverse, log, $1/\mu^2$ and sqrt.

The function can be used to create a power link function.

list("power") can be used to create a power link function.

Non-NULL weights can be used to indicate that different observations have different dispersions (with the values in weights being inversely proportional to the dispersions); or equivalently, when the elements of weights are positive integers w_i , that each response y_i is the mean of w_i unit-weight observations.

Value

`valsPredict` `nrow(dataPredictY) * nt` matrix of the predicted values

`list("coeffs")` If the coefficients of the eXplanatory variables were requested:
i.e. `keepcoeffs=TRUE`.
`ncol(dataX) * 1` matrix of the coefficients of the the eXplanatory variables

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFDs/article/view/215>

See Also

[PLS_beta](#) for more detailed results, [PLS_beta_kfoldcv](#) for cross validating models and [PLS_lm_wvc](#) for the same function dedicated to plsR models

Examples

```
data("GasolineYield", package="betareg")
yGasolineYield <- GasolineYield$yield
XGasolineYield <- GasolineYield[,2:5]
modpls <- PLS_beta_wvc(yGasolineYield, XGasolineYield, nt=3, modele="pls-beta")
modpls
rm("modpls")
```

print.plsRbetamodel *Print method for plsRbeta models*

Description

This function provides a print method for the class "plsRbetamodel"

Usage

```
## S3 method for class 'plsRbetamodel'  
print(x, ...)
```

Arguments

x	an object of the class "plsRbetamodel"
...	not used

Value

NULL

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[print](#)

Examples

```
data("GasolineYield", package="betareg")  
modpls <- plsRbeta(yield~., data=GasolineYield, nt=3, modele="pls-beta")  
print(modpls)
```

```
print.summary.plsRbetamodel
```

Print method for summaries of plsRbeta models

Description

This function provides a print method for the class "summary.plsRbetamodel"

Usage

```
## S3 method for class 'summary.plsRbetamodel'  
print(x, ...)
```

Arguments

x	an object of the class "summary.plsRbetamodel"
...	not used

Value

language	call of the model
----------	-------------------

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[print](#) and [summary](#)

Examples

```
data("GasolineYield", package="betareg")  
modpls <- plsRbeta(yield~., data=GasolineYield, nt=3, modele="pls-beta")  
print(summary(modpls))
```

simul_data_UniYX_beta *Data generating function for univariate beta plsR models*

Description

This function generates a single univariate rate response value Y and a vector of explanatory variables (X_1, \dots, X_{totdim}) drawn from a model with a given number of latent components.

Usage

```
simul_data_UniYX_beta(  
  totdim,  
  ncomp,  
  disp = 1,  
  link = "logit",  
  type = "a",  
  phi0 = 20  
)
```

Arguments

totdim	Number of columns of the X vector (from ncomp to hardware limits)
ncomp	Number of latent components in the model (from 2 to 6)
disp	Tune the shape of the beta distribution (defaults to 1)
link	Character specification of the link function in the mean model (μ). Currently, "logit", "probit", "cloglog", "cauchit", "log", "loglog" are supported. Alternatively, an object of class "link-glm" can be supplied.
type	Simulation scheme
phi0	Simulation scheme "a" parameter

Details

This function should be combined with the replicate function to give rise to a larger dataset. The algorithm used is a modification of a port of the one described in the article of Li which is a multivariate generalization of the algorithm of Naes and Martens.

Value

vector $(Y, X_1, \dots, X_{totdim})$

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

- Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>
- T. Naes, H. Martens (1985). Comparison of prediction methods for multicollinear data. *Commun. Stat., Simul.*, **14**:545-576. <doi:10.1080/03610918508812458>
- Baibing Li, Julian Morris, Elaine B. Martin (2002). Model selection for partial least squares regression, *Chemometrics and Intelligent Laboratory Systems*, **64**:79-89. <doi:10.1016/S0169-7439(02)00051-5>

See Also

[simul_data_UniYX](#)

Examples

```
# logit link
layout(matrix(1:4,nrow=2))
hist(t(replicate(100,simul_data_UniYX_beta(4,4)))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=3)))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=5)))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=15)))[,1])
layout(1)

# probit link
layout(matrix(1:4,nrow=2))
hist(t(replicate(100,simul_data_UniYX_beta(4,4,link="probit")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=3,link="probit")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=5,link="probit")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=15,link="probit")))[,1])
layout(1)

# cloglog link
layout(matrix(1:4,nrow=2))
hist(t(replicate(100,simul_data_UniYX_beta(4,4,link="cloglog")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=3,link="cloglog")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=5,link="cloglog")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=15,link="cloglog")))[,1])
layout(1)

# cauchit link
layout(matrix(1:4,nrow=2))
hist(t(replicate(100,simul_data_UniYX_beta(4,4,link="cauchit")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=3,link="cauchit")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=5,link="cauchit")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=15,link="cauchit")))[,1])
layout(1)
```

```
# loglog link
layout(matrix(1:4,nrow=2))
hist(t(replicate(100,simul_data_UniYX_beta(4,4,link="loglog")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=3,link="loglog")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=5,link="loglog")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=15,link="loglog")))[,1])
layout(1)

# log link
layout(matrix(1:4,nrow=2))
hist(t(replicate(100,simul_data_UniYX_beta(4,4,link="log")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=3,link="log")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=5,link="log")))[,1])
hist(t(replicate(100,simul_data_UniYX_beta(4,4,disp=15,link="log")))[,1])
layout(1)
```

summary.plsRbetamodel *Summary method for plsRbeta models*

Description

This function provides a summary method for the class "plsRbetamodel"

Usage

```
## S3 method for class 'plsRbetamodel'
summary(object, ...)
```

Arguments

object	an object of the class "plsRbetamodel"
...	further arguments to be passed to or from methods.

Value

call	function call of plsR beta models
------	-----------------------------------

Author(s)

Frédéric Bertrand
<frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also

[summary](#)

Examples

```
data("GasolineYield", package="betareg")
modpls <- plsRbeta(yield~., data=GasolineYield, nt=3, modele="pls-beta")
summary(modpls)
```

tilt.bootplsbeta

Non-parametric tilted bootstrap for PLS beta regression models

Description

Provides a wrapper for the bootstrap function `tilt.boot` from the `boot` R package. Implements non-parametric tilted bootstrap for PLS beta regression models by case resampling : the `tilt.boot` function will run an initial bootstrap with equal resampling probabilities (if required) and will use the output of the initial run to find resampling probabilities which put the value of the statistic at required values. It then runs an importance resampling bootstrap using the calculated probabilities as the resampling distribution.

Usage

```
tilt.bootplsbeta(  
  object,  
  typeboot = "plsmodel",  
  statistic = coefs.plsRbeta,  
  R = c(499, 250, 250),  
  alpha = c(0.025, 0.975),  
  sim = "ordinary",  
  stype = "i",  
  index = 1  
)
```

Arguments

object	An object of class <code>plsRbetamodel</code> to bootstrap
typeboot	The type of bootstrap. Either (Y,X) bootstrap (<code>typeboot="plsmode1"</code>) or (Y,T) bootstrap (<code>typeboot="fmode1_np"</code>). Defaults to (Y,T) resampling.
statistic	A function which when applied to data returns a vector containing the statistic(s) of interest. <code>statistic</code> must take at least two arguments. The first argument passed will always be the original data. The second will be a vector of indices, frequencies or weights which define the bootstrap sample. Further, if predictions are required, then a third argument is required which would be a vector of the random indices used to generate the bootstrap predictions. Any further arguments can be passed to <code>statistic</code> through the <code>...</code> argument.
R	The number of bootstrap replicates. Usually this will be a single positive integer. For importance resampling, some resamples may use one set of weights and others use a different set of weights. In this case R would be a vector of integers where each component gives the number of resamples from each of the rows of weights.
alpha	The alpha level to which tilting is required. This parameter is ignored if <code>R[1]</code> is 0 or if <code>theta</code> is supplied, otherwise it is used to find the values of <code>theta</code> as quantiles of the initial uniform bootstrap. In this case <code>R[1]</code> should be large enough that $\min(c(\alpha, 1-\alpha)) * R[1] > 5$, if this is not the case then a warning is generated to the effect that the <code>theta</code> are extreme values and so the tilted output may be unreliable.
sim	A character string indicating the type of simulation required. Possible values are "ordinary" (the default), "balanced", "permutation", or "antithetic".
stype	A character string indicating what the second argument of <code>statistic</code> represents. Possible values of <code>stype</code> are "i" (indices - the default), "f" (frequencies), or "w" (weights).
index	The index of the statistic of interest in the output from <code>statistic</code> . By default the first element of the output of <code>statistic</code> is used.

Value

An object of class "boot".

Author(s)

Frédéric Bertrand
 <frederic.bertrand@utt.fr>
<https://fbertran.github.io/homepage/>

References

Frédéric Bertrand, Nicolas Meyer, Michèle Beau-Faller, Karim El Bayed, Izzie-Jacques Namer, Myriam Maumy-Bertrand (2013). Régression Bêta PLS. *Journal de la Société Française de Statistique*, **154**(3):143-159. <http://publications-sfds.math.cnrs.fr/index.php/J-SFdS/article/view/215>

See Also[tilt.boot](#)**Examples**

```
data("GasolineYield", package="betareg")

GazYield.tilt.boot <- tilt.bootplsbeta(plsRbeta(yield~., data=GasolineYield, nt=3,
model="pls-beta"), statistic=coefs.plsRbeta, R=c(499, 100, 100),
alpha=c(0.025, 0.975), sim="balanced", stype="i", index=1)
boxplots.bootpls(GazYield.tilt.boot, 1:2)
```

TxTum

Cancer infiltration rates

Description

This dataset features cancer infiltration rates and microsatellites data.

Usage

TxTum

Format

A data frame with 106 rows and 60 variables.

CELTUMCO a numeric vector

age a numeric vector

sexe a numeric vector

HISTOADK a numeric vector

H2 a numeric vector

P3 a numeric vector

P4 a numeric vector

E1 a numeric vector

P5 a numeric vector

R10 a numeric vector

C3M a numeric vector

P6 a numeric vector

RB a numeric vector

FL7A a numeric vector
P53 a numeric vector
W2 a numeric vector
P2 a numeric vector
P1 a numeric vector
W4 a numeric vector
MT1 a numeric vector
MT2 a numeric vector
MT4 a numeric vector
MT3 a numeric vector
HLA a numeric vector
HLD a numeric vector
HLC a numeric vector
HLB a numeric vector
EA1 a numeric vector
EA3 a numeric vector
EA2 a numeric vector
EA4 a numeric vector
EB1 a numeric vector
EB2 a numeric vector
EB3 a numeric vector
EB4 a numeric vector
EGF1 a numeric vector
EGF2 a numeric vector
EGF3 a numeric vector
EGF4 a numeric vector
EGF5 a numeric vector
EGF6 a numeric vector
FL7B a numeric vector
VSFGF7 a numeric vector
F3A a numeric vector
F3B a numeric vector
VSFGFR3 a numeric vector
F4 a numeric vector
Q5 a numeric vector
VSTOP1 a numeric vector
VSTOP2A a numeric vector

VSEGFR a numeric vector
AFRAEGFR a numeric vector
SRXRA a numeric vector
SMT a numeric vector
QMTAMPN a numeric vector
QMTDELN a numeric vector
SHL a numeric vector
SEA a numeric vector
SEB a numeric vector
QPCRFGF7 a numeric vector

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data
print(TxTum)
summary(TxTum)
```

TxTum.mod.bootBC1	<i>Bootstrap distribution TxTum BC1 model A precomputed bootstrap distribution of the coefficients of a model used in the vignette.</i>
-------------------	---

Description

Bootstrap distribution TxTum BC1 model

A precomputed bootstrap distribution of the coefficients of a model used in the vignette.

Usage

```
TxTum.mod.bootBC1
```

Format

a class boot object

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(TxTum.mod.bootBC1)
str(TxTum.mod.bootBC1)
plot(TxTum.mod.bootBC1)
```

TxTum.mod.bootBR6	<i>Bootstrap distribution TxTum BR6 model A precomputed bootstrap distribution of the coefficients of a model used in the vignette.</i>
-------------------	---

Description

Bootstrap distribution TxTum BR6 model

A precomputed bootstrap distribution of the coefficients of a model used in the vignette.

Usage

```
TxTum.mod.bootBR6
```

Format

a class boot object

References

Régression Bêta PLS. (French) [PLS Beta regression.], F. Bertrand, N. Meyer, M. Beau-Faller, K. El Bayed, N. Izzie-J., M. Maumy-Bertrand, (2013), J. SFdS, 154(3):143-159

Partial Least Squares Regression for Beta Regression Models. F. Bertrand, M. Maumy (2021). useR! 2021, Zurich.

Examples

```
data(TxTum.mod.bootBR6)
str(TxTum.mod.bootBR6)
plot(TxTum.mod.bootBR6)
```

Index

- * **datagen**
 - simul_data_UniYX_beta, 66
 - * **datasets**
 - colon, 11
 - ind_BCa_nt1BC, 17
 - ind_BCa_nt1BR, 17
 - ind_BCa_nt2BC, 18
 - ind_BCa_nt2BR, 19
 - ind_BCa_nt3, 19
 - ind_BCa_nt3BC, 20
 - ind_BCa_nt3BR, 21
 - ind_BCa_nt4BC, 21
 - ind_BCa_nt4BR, 22
 - ind_BCa_nt5BC, 23
 - ind_BCa_nt5BR, 23
 - ind_BCa_nt6BC, 24
 - ind_BCa_nt6BR, 25
 - modpls.boot3, 29
 - modpls_sub4, 30
 - TxTum, 71
 - TxTum.mod.bootBC1, 73
 - TxTum.mod.bootBR6, 74
 - * **methods**
 - print.plsRbetamodel, 64
 - print.summary.plsRbetamodel, 65
 - summary.plsRbetamodel, 68
 - * **models**
 - bootplsbeta, 3
 - coefs.plsRbeta, 7
 - coefs.plsRbeta.raw, 8
 - coefs.plsRbetanp, 10
 - kfolds2Chisq, 25
 - kfolds2Chisqind, 27
 - kfolds2CVinfos_beta, 28
 - permcoefs.plsRbeta, 31
 - permcoefs.plsRbeta.raw, 32
 - permcoefs.plsRbetanp, 34
 - PLS_beta, 39
 - PLS_beta_formula, 43
 - PLS_beta_kfoldcv, 49
 - PLS_beta_kfoldcv_formula, 54
 - PLS_beta_wvc, 60
 - plsRbeta, 35
 - tilt.bootplsbeta, 69
 - * **print**
 - print.plsRbetamodel, 64
 - print.summary.plsRbetamodel, 65
 - summary.plsRbetamodel, 68
 - * **regression**
 - kfolds2Chisq, 25
 - kfolds2Chisqind, 27
 - kfolds2CVinfos_beta, 28
 - PLS_beta, 39
 - PLS_beta_formula, 43
 - PLS_beta_kfoldcv, 49
 - PLS_beta_kfoldcv_formula, 54
 - PLS_beta_wvc, 60
 - plsRbeta, 35
 - * **utilities**
 - simul_data_UniYX_beta, 66
- as.data.frame, 36, 44, 55
- boot, 4, 5
- bootplsbeta, 3, 8, 10, 11, 32, 33, 35
- coefs.plsRbeta, 7
- coefs.plsRbeta.raw, 8
- coefs.plsRbetanp, 10
- colon, 11
- family, 36, 40, 44, 50, 55, 61
- formula, 35, 44, 55
- glm, 37, 41, 47, 51, 58, 62
- glm.control, 37, 47, 57
- ind_BCa_nt1BC, 17
- ind_BCa_nt1BR, 17
- ind_BCa_nt2BC, 18

ind_BCa_nt2BR, 19
ind_BCa_nt3, 19
ind_BCa_nt3BC, 20
ind_BCa_nt3BR, 21
ind_BCa_nt4BC, 21
ind_BCa_nt4BR, 22
ind_BCa_nt5BC, 23
ind_BCa_nt5BR, 23
ind_BCa_nt6BC, 24
ind_BCa_nt6BR, 25

kfolds2Chisq, 25, 27
kfolds2Chisqind, 26, 27
kfolds2coeff, 26, 27, 29, 53, 60
kfolds2CVinfos_beta, 28, 53, 60
kfolds2Mclassified, 26, 27, 29, 53, 60
kfolds2Mclassifiedind, 26, 27, 29, 53, 60
kfolds2Press, 26, 27, 29, 53, 60
kfolds2Pressind, 26, 27, 29, 53, 60

model.offset, 36, 45, 56
modpls.boot3, 29
modpls_sub4, 30

offset, 36, 45, 56

permcoefs.plsRbeta, 31
permcoefs.plsRbeta.raw, 32
permcoefs.plsRbetanp, 34
PLS_beta, 39, 63
PLS_beta_formula, 43
PLS_beta_kfoldcv, 26–28, 43, 49, 63
PLS_beta_kfoldcv_formula, 49, 54
PLS_beta_wvc, 43, 49, 60
PLS_glm_kfoldcv_formula, 62
PLS_lm_wvc, 63
plsR, 39
plsRbeta, 8–10, 31, 33, 34, 35
plsRbeta-package, 3
plsRbetamodel.default (plsRbeta), 35
plsRbetamodel.formula (plsRbeta), 35
plsRglm, 39
print, 64, 65
print.plsRbetamodel, 64
print.summary.plsRbetamodel, 65

simul_data_UniYX, 67
simul_data_UniYX_beta, 66
summary, 65, 69
summary.plsRbetamodel, 68
tilt.boot, 71
tilt.bootplsbeta, 69
TxTum, 71
TxTum.mod.bootBC1, 73
TxTum.mod.bootBR6, 74