

Package ‘semmcci’

December 17, 2022

Title Monte Carlo Confidence Intervals in Structural Equation Modeling

Version 1.0.4

Description Monte Carlo confidence intervals for free and defined parameters in models fitted in the structural equation modeling package 'lavaan' can be generated using the 'semmcci' package. 'semmcci' has two main functions, namely, MC() and MCStd(). The output of 'lavaan' is passed as the first argument to the MC() function to generate Monte Carlo confidence intervals. Monte Carlo confidence intervals for the standardized estimates can also be generated by passing the output of the MC() function to the MCStd() function. Preacher and Selig (2012) <[doi:10.1080/19312458.2012.679848](https://doi.org/10.1080/19312458.2012.679848)>.

URL <https://github.com/jeksterslab/semmcci>,
<https://jeksterslab.github.io/semmcci/>

BugReports <https://github.com/jeksterslab/semmcci/issues>

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 3.0.0)

Imports stats, methods, lavaan

Suggests knitr, rmarkdown, testthat, MASS

RoxygenNote 7.2.3

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<<https://orcid.org/0000-0003-4818-8420>>),
Shu Fai Cheung [ctb] (<<https://orcid.org/0000-0002-9871-9448>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Repository CRAN

Date/Publication 2022-12-17 09:50:02 UTC

R topics documented:

coef.semmcci	2
coef.semmccistd	3
confint.semmcci	5
confint.semmccistd	6
MC	7
MCStd	9
print.semmcci	11
print.semmccistd	12
summary.semmcci	14
summary.semmccistd	15
vcov.semmcci	16
vcov.semmccistd	18

Index	20
--------------	-----------

coef.semmcci	<i>Parameter Estimates</i>
--------------	----------------------------

Description

Parameter Estimates

Usage

```
## S3 method for class 'semmcci'
coef(object, ...)
```

Arguments

object	Object of class semmcci.
...	additional arguments.

Value

Returns a vector of parameter estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```

library(semmcci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)
coef(unstd)

```

coef.semmccistd

*Standardized Parameter Estimates***Description**

Standardized Parameter Estimates

Usage

```

## S3 method for class 'semmccistd'
coef(object, ...)

```

Arguments

object Object of class semmccistd.
 ... additional arguments.

Value

Returns a vector of standardized parameter estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
library(semccci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model, fixed.x = FALSE)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)

# Standardized Monte Carlo -----
std <- MCStd(unstd)
coef(std)
```

confint.semmcci *Monte Carlo Confidence Intervals for the Parameter Estimates*

Description

Monte Carlo Confidence Intervals for the Parameter Estimates

Usage

```
## S3 method for class 'semmcci'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object	Object of class semmcci.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
library(semmcci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)
```

```

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)
confint(unstd)

```

confint.semmccistd *Monte Carlo Confidence Intervals for the Standardized Parameter Estimates*

Description

Monte Carlo Confidence Intervals for the Standardized Parameter Estimates

Usage

```
## S3 method for class 'semmccistd'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object	Object of class <code>semmccistd</code> .
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```

library(semccci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model, fixed.x = FALSE)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)

# Standardized Monte Carlo -----
std <- MCStd(unstd)
confint(std)

```

Description

Calculates Monte Carlo confidence intervals for free and defined parameters.

Usage

```
MC(
```

```

object,
R = 20000L,
alpha = c(0.001, 0.01, 0.05),
decomposition = "eigen",
pd = TRUE,
tol = 1e-06
)

```

Arguments

object	object of class lavaan.
R	Positive integer. Number of Monte Carlo replications.
alpha	Numeric vector. Significance level α . Default value is <code>alpha = c(0.001, 0.01, 0.05)</code> .
decomposition	Character string. Matrix decomposition of the sampling variance-covariance matrix for the data generation. If <code>decomposition = "chol"</code> , use Cholesky decomposition. If <code>decomposition = "eigen"</code> , use eigenvalue decomposition. If <code>decomposition = "svd"</code> , use singular value decomposition.
pd	Logical. If <code>pd = TRUE</code> , check if the sampling variance-covariance matrix is positive definite using <code>tol</code> .
tol	Numeric. Tolerance used for <code>pd</code> .

Details

A sampling distribution of parameter estimates is generated from the multivariate normal distribution using the parameter estimates and the sampling variance-covariance matrix. Confidence intervals for free and defined parameters are generated using the simulated sampling distribution. Parameters can be defined using the `:=` operator in the lavaan model syntax.

Value

Returns an object of class `semmcci` which is a list with the following elements:

`R` Number of Monte Carlo replications.

`alpha` Significance level α specified.

`lavaan` lavaan object.

`decomposition` Matrix decomposition used to generate multivariate normal random variates.

`thetahat` Parameter estimates $\hat{\theta}$.

`thetahatstar` Sampling distribution of parameter estimates $\hat{\theta}^*$.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```

library(semccci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model)

# Monte Carlo -----
MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)

```

MCStd

Standardized Monte Carlo Confidence Intervals

Description

Calculates standardized Monte Carlo confidence intervals for free and defined parameters.

Usage

```
MCStd(object, alpha = c(0.001, 0.01, 0.05))
```

Arguments

object object of class semccci. Output of the MC() function.

`alpha` Numeric vector. Significance level α . Default value is `alpha = c(0.001, 0.01, 0.05)`.

Details

The empirical sampling distribution of parameter estimates from the argument object is standardized, that is, each randomly generated vector of parameters is standardized. Defined parameters are computed from the standardized component parameters. Confidence intervals are generated using the standardized empirical sampling distribution.

Value

Returns an object of class `semmccistd` which is a list with the following elements:

`R` Number of Monte Carlo replications.

`alpha` Significance level α specified.

`lavaan` lavaan object.

`decomposition` Matrix decomposition used to generate multivariate normal random variates.

`thetahat` Parameter estimates $\hat{\theta}$.

`thetahatstar` Sampling distribution of parameter estimates $\hat{\theta}^*$.

`ci` Confidence intervals.

`thetahat_std` Standardized parameter estimates $\hat{\theta}_{std}$.

`thetahatstar_std` Standardized sampling distribution of parameter estimates $\hat{\theta}_{std}^*$.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
library(semmcci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
```

```

Y ~ cp * X + b * M
M ~ a * X
indirect := a * b
direct := cp
total := cp + (a * b)
"
fit <- sem(data = df, model = model, fixed.x = FALSE)

# Monte Carlo -----
output <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)

# Standardized Monte Carlo -----
MCStd(output)

```

```
print.semmcci      Print Method for Object of Class semmcci
```

Description

Print Method for Object of Class semmcci

Usage

```
## S3 method for class 'semmcci'
print(x, digits = 4, ...)
```

Arguments

x	an object of class semmcci.
digits	Integer indicating the number of decimal places to display.
...	further arguments.

Value

Returns a matrix of estimates, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```

library(semmcci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)
print(unstd)

```

```
print.semmccistd      Print Method for Object of Class semmccistd
```

Description

Print Method for Object of Class `semmccistd`

Usage

```
## S3 method for class 'semmccistd'
print(x, digits = 4, ...)
```

Arguments

`x` an object of class `semmccistd`.
`digits` Integer indicating the number of decimal places to display.
`...` further arguments.

Value

Returns a matrix of estimates, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
library(semmcci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model, fixed.x = FALSE)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)

# Standardized Monte Carlo -----
```

```
std <- MCStd(unstd)
print(std)
```

```
summary.semmcci      Summary Method for an Object of Class semmcci
```

Description

Summary Method for an Object of Class semmcci

Usage

```
## S3 method for class 'semmcci'
summary(object, digits = 4, ...)
```

Arguments

object	Object of class semmcci.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of estimates, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
library(semmcci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)
```

```

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)
summary(unstd)

```

summary.semmccistd *Summary Method for an Object of Class semmccistd*

Description

Summary Method for an Object of Class semmccistd

Usage

```
## S3 method for class 'semmccistd'
summary(object, digits = 4, ...)
```

Arguments

object	Object of class semmccistd.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of estimates, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```

library(semmcci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model, fixed.x = FALSE)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)

# Standardized Monte Carlo -----
std <- MCStd(unstd)
summary(std)

```

vcov.semmcci

*Sampling Covariance Matrix of the Parameter Estimates***Description**

Sampling Covariance Matrix of the Parameter Estimates

Usage

```

## S3 method for class 'semmcci'
vcov(object, ...)

```


Arguments

object Object of class semmccistd.
 ... additional arguments.

Value

Returns a matrix of the variance-covariance matrix of parameter estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
library(semmcci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
  direct := cp
  total := cp + (a * b)
"
fit <- sem(data = df, model = model)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)
vcov(unstd)
```

vcov.semmccistd

*Sampling Covariance Matrix of the Standardized Parameter Estimates***Description**

Sampling Covariance Matrix of the Standardized Parameter Estimates

Usage

```
## S3 method for class 'semmccistd'
vcov(object, ...)
```

Arguments

```
object      Object of class semmccistd.
...         additional arguments.
```

Value

Returns a matrix of the variance-covariance matrix of standardized parameter estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
library(semmcci)
library(lavaan)

# Generate Data -----
n <- 1000
a <- 0.50
b <- 0.50
cp <- 0.25
s2_em <- 1 - a^2
s2_ey <- 1 - cp^2 - a^2 * b^2 - b^2 * s2_em - 2 * cp * a * b
em <- rnorm(n = n, mean = 0, sd = sqrt(s2_em))
ey <- rnorm(n = n, mean = 0, sd = sqrt(s2_ey))
X <- rnorm(n = n)
M <- a * X + em
Y <- cp * X + b * M + ey
df <- data.frame(X, M, Y)

# Fit Model in lavaan -----
model <- "
  Y ~ cp * X + b * M
  M ~ a * X
  indirect := a * b
```

```
    direct := cp
    total := cp + (a * b)
  "
fit <- sem(data = df, model = model, fixed.x = FALSE)

# Monte Carlo -----
unstd <- MC(
  fit,
  R = 100L, # use a large value e.g., 20000L for actual research
  alpha = c(0.001, 0.01, 0.05)
)

# Standardized Monte Carlo -----
std <- MCStd(unstd)
vcov(std)
```

Index

* **mc**

MC, [7](#)

MCSStd, [9](#)

* **method**

coef.semmcci, [2](#)

coef.semmccistd, [3](#)

confint.semmcci, [5](#)

confint.semmccistd, [6](#)

print.semmcci, [11](#)

print.semmccistd, [12](#)

summary.semmcci, [14](#)

summary.semmccistd, [15](#)

vcov.semmcci, [16](#)

vcov.semmccistd, [18](#)

coef.semmcci, [2](#)

coef.semmccistd, [3](#)

confint.semmcci, [5](#)

confint.semmccistd, [6](#)

MC, [7](#)

MCSStd, [9](#)

print.semmcci, [11](#)

print.semmccistd, [12](#)

summary.semmcci, [14](#)

summary.semmccistd, [15](#)

vcov.semmcci, [16](#)

vcov.semmccistd, [18](#)